NOTICE TO WATER WELL CONTRACTOR

ST

OTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the STATE OF OREGON JUL 2 5 1975 State Well No.	75/2W-29ab
rate engineer, salem, oregon 9/310 (Please type or print) R RESOURCES Death Permit No. within 30 days from the date of well completion.	<u>G-6958</u>

1) OWNER:	(10) LOCATION OF WELL:	-ham
Name Tryin Richard Reinhard	County Marion Driller's well nun	
Address 3685 Monroe NE	1/4 1/4 Section 29 T. 7S I	and the second of the second o
Salem. Oregon	Bearing and distance from section or subdivision	n corner
(2) TYPE OF WORK (check):		
New Well ☑ Deepening □ Reconditioning □ Abandon □		· · · · · · · · · · · · · · · · · · ·
f abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed we	all.
(3) TYPE OF WELL: (4) PROPOSED USE (check):		37 ft.
Rotary Driven Domestic Dindustrial Municipal D		rface. Date 7_17-75
Table DV Tofford		
Dug	Artesian pressure lbs. per square	
CASING INSTALLED: Threaded □ Welded ☑	(12) WELL LOG: Diameter of well be	elow casing
8 " Diam. from top ft. to 84 ft. Gage 250	Depth drilled 84 ft. Depth of comple	ted well 84 ft.
" Diam. fromft. toft. Gage	Formation: Describe color texture grain size a	nd structure of materials;
" Diam. fromft. toft. Gage	and show thickness and nature of each stratum	i and adulier peneiraled,
	with at least one entry for each change of format position of Static Water Level and indicate princ	cipal water-bearing strata.
PERFORATIONS: Perforated? Tyes X No.	MATERIAL	From To SWL
Type of perforator used		
Size of perforations in. by in.	Top Soil	2 37
nerforations from ft. to ft.	Brown Silty Clay	37 45
perforations fromft. toft.	Dark Brown sand & gravel	45 47
perforations from ft. to ft.	Gray Silty Clay	47 49
	Brown sand and gravel	49 59
(7) SCREENS: Well screen installed? Yes No	Very Silty sand some gravel Blue Cemented sand & gravel	59 65
Manufacturer's Name	Brown cemented sand & gravel	65 84
Type Model No ft. to ft.	Brown cemenced band & graver	
Diam. Slot size Set from ft. to ft.		
(8) WELL TESTS: Drawdown is amount water level is lowered below static level		
Was a pump test made? ☐ Yes № No If yes, by whom?		
Yield: gal./min. with ft. drawdown after hrs.		
" "		
" " "		
Bailer test 50 gal./min. with 5 ft. drawdown after 1 hrs.		
Artesian flow g.p.m.		
uperature of water Depth artesian flow encountered ft.	Work started 7-12-75 19 Complete	
(9) CONSTRUCTION:	Date well drilling machine moved off of well	7-17-75 19
	Drilling Machine Operator's Certification	
Well seal—Material usedCement	This well was constructed under my Materials used and information reported	above are true to my
Well sealed from land surface to	1 t less overlodes and hollot	
Diameter of well bore to bottom or seal	reigned Dallas & Dells	Date 7-18-75, 19
Number of sacks of cement used in well seal8sacks	(Drilling Machine Operator) Drilling Machine Operator's License No.	
Number of sacks of bentonite used in well sealsacks	Drilling Machine Operator's License No.	
Brand name of bentonite	Water Well Contractor's Certification:	
Number of pounds of bentonite per 100 gallons	This well was drilled under my jurisc	diction and this report is
of waterlbs./100 gals.	true to the best of my knowledge and be	ener.
Was a drive shoe used? ☼ Yes ☐ No Plugs Size: location ft.	Name WILLAMET'TE DRILLING COM	PANY
Did any strata contain unusable water? 🗌 Yes 🔁 No	, , , , , , , , , , , , , , , , , , , ,	
Type of water? depth of strata	Address 1450 Barnick Road NE	Daten oregon
Method of sealing strata off	[Signed] Emel O. Du	(N)
Was well gravel packed? ☐ Yes ₹☐ No Size of gravel:	(Water Well Con	
Gravel placed from ft. to ft.	Contractor's License No2 Date	/mlsm/5, 19