MARI 66136

STATE OF OREGON WATER SUPPLY WELL REPORT

Mari 66136

WELL I.D. LABEL# L 120744 **START CARD #** 213030

(as required by ORS 557.765 & OAR 690-205-0210)	URIGINAL LUG#
(1) LAND OWNER Owner Well I.D.	
First Name Last Name	(9) LOCATION OF WELL (legal description)
Company HILAND WATER CORPORATION	County MARION Twp 6 S N/S Range 2 W E/W WM
Address 23875 NE DILLON RD.	Sec 30 SW 1/4 of the NE 1/4 Tax Lot 1200
City NEWBERG State OR Zip 97132	Tax Man Number
(2) TYPE OF WORK New Well Deepening Conversion	Tax Map Number Lot Lat o ' " or DMS or DD Long o ' " or DMS or DD
X Alteration (complete 2a & 10) Abandonment(complete 5a)	Long " " or DMS or DD
(2a) PRE-ALTERATION Dia + From To Gauge Stl Plstc Wld Thrd	Street address of well Nearest address
Casing: 6 Gauge St. 11ste Wid 11md	\[\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \
Material From To Amt sacks/lbs	7042 PORTLAND RD. NE, SALEM, OR 97305
Seal:	
(3) DRILL METHOD	(10) STATIC WATER LEVEL
Rotary Air Rotary Mud Cable Auger Cable Mud	Date SWL(psi) + SWL(ft) Existing Well / Pre-Alteration
Reverse RotaryOther	Completed Well 03-09-2016 32
(4) PROPOSED USE Domestic Irrigation Community	Flowing Artesian? Dry Hole?
Industrial/ Commercial Livestock Dewatering	
Thermal Injection Other	· -
	20110W 2WZ(N)
(5) BORE HOLE CONSTRUCTION Special Standard (Attach copy)	03-09-2016 74 84 60 32
Depth of Completed Well 86 ft.	
BORE HOLE SEAL sacks/ Dia From To Material From To Amt lbs	
Dia From To Material From To Amt lbs 10 0 86 Cement 0 62 38 S	
Calculated 17.13	
	(1) WELV LOG
Calculated	(11) WELL LOG Ground Elevation
How was seal placed: Method A B XC D E	Material From To
Other	EXISTING WELL REPAIR:
Backfill placed from ft. to ft. Material sand/gravel Size 1/8x1/4	EAISTING WELL REPAIR.
<u> </u>	EXISTING 6" CASING OVERDRILLED AND
Explosives used: Yes Type Amount	REMOVED FROM BORE
(5a) ABANDONMENT USING UNHYDRATED BENTONITE	BORE REDRILLED 10" DIA. TO BOTTOM 0 86
Proposed Amount Pounds Actual Amount Pounds	NEW 6" CASING & SCREEN INSTALLED
(6) CASING/LINER_	86 FT. TO +2.5 FT.
Casing Liner Dia + From To Gauge Stl Plstc Wld Thrd	SCREEN GRAVELED PACKED 86 62 REMAINING BORE GROUTRD WITH CEMENT 62 0
	REMAIN (INC DOLLS GROOTED WITH CEMELY)
● 6 □ 84 86 .250 ● X	RECEIVED BY OWRD
	TILOZIVES D. OTT
Shoe Inside Outside Other Location of shoe(s)	MAR 1 5 2016
Temp casing Yes Dia From To	
(7) PERFORATIONS/SCREENS Perforations Method	SALEM, OR
Screens Type WOUNDWIRE Material STAINLESS STL.	Date Started02-25-2016 Completed 03-09-2016
Perf/S Casing/ Screen Scrn/slot Slot # of Tele/	
creen Liner Dia From To width length slots pipe size Screen Casing 6 74 84 .03	(unbonded) Water Well Constructor Certification
Screen Casing 6 74 64 .05	I certify that the work I performed on the construction, deepening, alteration, or abandonment of this well is in compliance with Oregon water supply well
	construction standards. Materials used and information reported above are true to
	the best of my knowledge and belief.
	License Number Date
(8) WELL TESTS: Minimum testing time is 1 hour	
Pump Bailer (Air Flowing Artesian	Signed
Yield gal/min Drawdown Drill stem/Pump depth Duration (hr)	(bonded) Water Well Constructor Certification
B 36 13 1	I accept responsibility for the construction, deepening, alteration, or abandonment
A 45 60 2	work performed on this well during the construction dates reported above. All work
A 60 70	performed during this time is in compliance with Oregon water supply well
Temperature 57 °F Lab analysis Yes By	construction standards. This report is true to the best of my knowledge and belief.
Water quality concerns? Yes (describe below) TDS amount From To Description Amount Units	License Number 1266 Date 03-10-2016
From To Description Amount Units	Signed Sulli
	Contact Info (optional)
	Common and