WATER WELL REPORT
STATE OF OREGON

MARI 676

4-8-83

RECEIVED
APR 18 1983
WATER RESOURCES DEPT.
SALEM, OREGON

State Well No. 4S/1W-22bb

State Permit No.

(1) OWNER:
Name Byron Grim
Address 13122 Brookside Dr
City Aurora State Ore

(2) TYPE OF WORK (check):
New Well ☑ Deepening ☐ Reconditioning ☐ Abandon ☐
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:
Rotary Air ☐ Driven ☐
Rotary Mud ☐ Dug ☐
Cable ☑ Bored ☐

(4) PROPOSED USE (check):
Domestic ☑ Industrial ☐ Municipal ☐
Irrigation ☐ Test Well ☐ Other ☐
Thermal: Withdrawal ☐ Reinjection ☐

(5) CASING INSTALLED:
Steel ☑ Plastic ☐
Threaded ☐ Welded ☑
6" Diam. from +1 ft. to 107 ft. Gauge 250
" Diam. from ft. to ft. Gauge

LINER INSTALLED:
" Diam. from ft. to ft. Gauge

(6) PERFORATIONS:
Perforated? ☐ Yes ☑ No
Type of perforator used
Size of perforations in. by in.
perforations from ft. to ft.
perforations from ft. to ft.
perforations from ft. to ft.

(7) SCREENS:
Well screen installed? ☐ Yes ☑ No
Manufacturer's Name
Type Model No.
Diam. Slot Size Set from ft. to ft.
Diam. Slot Size Set from ft. to ft.

(8) WELL TESTS:
Drawdown is amount water level is lowered below static level

Was a pump test made? ☐ Yes ☑ No If yes, by whom?
gal./min. with ft. drawdown after hrs.
" " " "
Air test gal./min. with drill stem at ft. hrs.
Bailer test 40 gal./min. with 46 ft. drawdown after 1 hrs.
Artesian flow g.p.m.
Temperature of water Depth artesian flow encountered ft.

(9) CONSTRUCTION:
Special standards: Yes ☐ No ☑
Well seal—Material used Cement
Well sealed from land surface to 23 ft.
Diameter of well bore to bottom of seal 9+ in.
Diameter of well bore below seal 6 in.
Number of sacks of cement used in well seal 10 sacks
How was cement grout placed? Tremie

Was pump installed? Type HP Depth ft.
Was a drive shoe used? ☑ Yes ☐ No Plugs Size: location ft.
Did any strata contain unusable water? ☐ Yes ☐ No
Type of Water? depth of strata
Method of sealing strata off
Was well gravel packed? ☐ Yes ☑ No Size of gravel:
Gravel placed from ft. to ft.

(10) LOCATION OF WELL:
County Marion Driller's well number
NW ¼ NW ¼ Section 22 T. 4 R. 1W W.M.
Tax Lot # Lot Blk Subdivision
Address at well location:

(11) WATER LEVEL: Completed well.
Depth at which water was first found 94 ft.
Static level 98 ft. below land surface. Date 4-15-83
Artesian pressure lbs. per square inch. Date

(12) WELL LOG:
Diameter of well below casing —
Depth drilled 107 ft. Depth of completed well 107 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
Top Soil & Brown clay	0	38	
Light Blue Clay	38	46	
Darne Blue Silty Clay	46	74	
Gray Clay	74	94	
Fine black Sand	94	101	
Sand & Gravel	101	105	
Gravel	105	107	

Work started 4/8/83 19 Completed 4-15 1983
Date well drilling machine moved off of well 4-15 1983

Drilling Machine Operator's Certification:
This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.
[Signed] John W. Beck (Drilling Machine Operator) Date 4-15, 1983
Drilling Machine Operator's License No. 437

Water Well Contractor's Certification:
This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Name Beck Welldrilling (Person, firm or corporation) (Type or print)
Address 24137 S. Skylane Dr Canby Ore.
[Signed] John W. Beck (Water Well Contractor)
Contractor's License No. 449 Date 4-15, 1983

NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report are to be filed with the WATER RESOURCES DEPARTMENT, SALEM, OREGON 97310 within 30 days from the date of well completion.

SP*12658-690