The original and first the of this report are to MAY 3 = 1972 WATER WELL REPORT filed with the

State Well No.

state engineer, salem, oredon trade NGINEL please type or print)
within 30 days from the data LEM. OREGON
of well completion.

SP*45656-119

(1) OWNER;	(10) LQCATION OF WELL:
Name The Nickery Coxp.	County Masery Driller's well number
Address 1223 Edgewater St MW. 97304	1/4 1/4 Section & T. 75 R. 2 W W.M.
Selen.	Bearing and distance from section or subdivision corner
(2) TYPE OF WORK (check):	
New Well Deepening Reconditioning Abandon	
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 27 ft.
Botony Cl. Drivon Cl	
Cable	
Dug Bored I Irrigation Test Well Other	Artesian pressure lbs. per square inch. Date
(5) CASING INSTALLED: Threaded Welded	(12) WELL LOG: Diameter of well below casing
12 " Diam from + 1 ft. to 174 ft. Gage 250	Depth drilled / 24 ft. Depth of completed well / 24 ft.
ft. Gage	Formation: Describe color, texture, grain size and structure of materials;
	and show thickness and nature of each stratum and aquifer penetrated,
6) PERFORATIONS: Perforated? Tyes T No.	with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.
Type of perforator used	
Size of perforations /2 in. by in.	Brewn Clay Class 22 53
232 perforations from 85 ft. to 115 ft.	Life to the state of the state
456 perforations from 123 ft. to 160 ft.	Anall diane
perforations fromft. toft.	Santales States
(7) SCREENS: Well screen installed? Yes No	10 1 10 1 10 1 10 10 10 10 10 10 10 10 1
Manufacturer's Name	By sever Sand - Small Lower 73 88
Type Model No	Lunder Strand Vigner 15 82
Diam. Slot size Set from ft. to ft.	Theren Small
Diam. Slot size Set from ft. to ft.	Cemental Granel 91 103
	Small to med Gravel 103 113
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	Cemented Grovel. 113 117
Was a pump test made? Yes 🗌 No If yes, by whom?	Sand & Since Spacel 117 119
Yield: 535 gal./min. with 68 ft. drawdown after hrs.	Commented yeared 119 144
625 " 12/ " 74"	Small To Sange Garal 144 147
440 119 124 11	Comented Grand 147 174
Bailer test gal./min. with ft. drawdown after hrs.	
Artesian flow g.p.m.	2 95 00 1/1/ 70
Temperature of water Depth artesian flow encountered ft.	Work started 3 - 23 19 72 Completed 4- 1/ 19 72
(5) CONSTRUCTION:	Date well drilling machine moved off of well 4-12 1972
Company of Marine	Drilling Machine Operator's Certification:
	This well was constructed under my direct supervision.
Well sealed from land surface to	Materials used and information reported above are true to my best knowledge and belief.
Diameter of well hore to bottom of seal	Vi tare and Il FEBRUARE: 11/12 27
Diameter of well bore below seal in. Number of sacks of cement used in well seal sacks	[Signed] Date Date (Drilling Machine Operator)
Number of sacks of bentonite used in well sealsacks	Drilling Machine Operator's License No
Brand name of bentonite	TYPE AND THE CONTRACT OF THE C
Number of pounds of bentonite per 100 gallons	Water Well Contractor's Certification:
of water lbs./100 gals.	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Was a drive shoe used? Yes \(\subseteq No \) Plugs Size: location ft.	Name Rebin SON EDIA Prilling
Did any strata contain unusable water? Yes No	(Person, firm or corporation) (Type or print)
Type of water? depth of strata	Address 4510 VALLAS ITO M.W. SALE W
Method of sealing strata off	and the same of the same
Was well gravel packed? ☐ Yes ☑ No Size of gravel:	[Signed] (Water Well Contractor)
	Contractor's License No. 15 Date 4/12 1972
Gravel placed from ft. to ft.	COLLEGE OF DESCRIPTION OF THE PROPERTY OF TH