MARI 68554

R. Stadeli & Sons

STATE OF OREGON

Well & Pump, Inc. 4385 Stadeli Lane NE

WELL I.D. LABEL# L		
START CARD#	216541	
ORIGINAL LOG#	MARION	9193

WATER SUPPLY WELL REPORT	START CARD # 216541	
(as required by ORS 537.765 & OAR 690-205-0210) Silverton, O	R 97381 ORIGINAL LOG # MARION 9193	
(1) LAND OWNER Owner Well I.D. First Name Gene Last Name Beyer	MARI 68554	
	(9) LOCATION OF WELL (legal description)	
Company	County MARION Twp 3 S N/S Range 2 W E/W WM	
Address 10750 Edmunson Dr SE	Sec 1 NW 1/4 of the SE 1/4 Tax Lot 700	
City Salem State OR Zip 97317	Tax Map Number Lot	
(2) TYPE OF WORK New Well Deepening Conversion		
X Alteration (complete 2a & 10) Abandonment(complete 5a)	1	
(2a) PRE-ALTERATION	Long Om DMS or DD	
Dia + From To Gauge Stl Plstc Wld Thrd	Street address of well Nearest address	
Casing: 10 × 1 99 250 • C ×	Deschates Dr. Ole Address)	
Material From To Amt sacks/lbs	Deschutes Dr (No Address)	
Seal: Cement 0 99 Not on Log		
(3) DRILL METHOD	(10) STATIC WATER LEVEL	
X Rotary Air Rotary Mud X Cable Auger Cable Mud	Date SWL(psi) + SWL(ft)	
	Existing Well / Pre-Alteration 03-22-2019 130.7	
Reverse RotaryOther	Completed Well 05-02-2019 128.3	
(4) PROPOSED USE Domestic Irrigation Community	Flowing Artesian? Dry Hole?	
Industrial/Commericial Livestock Dewatering		
	WATER BEARING ZONES Depth water was first found Original	
ThermalInjectionOther	SWL Date From To Est Flow SWL(psi) + SWL(ft)	
(5) BORE HOLE CONSTRUCTION Special Standard (Attach copy)	No drilling performed	
Depth of Completed Well 395 ft.		
	See MARI 9193	
BORE HOLE SEAL sacks/		
Dia From To Material From To Amt Uss See MARI 193 for Orbinal Cement Grout 0 138 22 S		
Calculated 16.5		
Calculated	(11) WELL LOG Ground Flexation	
	Ground Elevation	
How was seal placed: Method A B C D E	Material From To	
Other	We installed 8" casing inside of the 10" borehole.	
Backfill placed from ft. to ft. Material	This was to satisfy a well construction condition of	
Filter pack from ft. to ft. Material Size	the water right. As per Joel Jeffrey email of April	
_	26, 2018, the OWRD wanted 8" casing sealed to	
Explosives used: Yes Type Amount	130 ft below ground surface.	
(5a) ABANDONMENT USING UNHYDRATED BENTONITE		
Proposed Amount Pounds Actual Amount Pounds	The drive shoe was installed to facilitate the pump	
/O CLASTRICITI TATORD	removal from catching on bottom of 8" casing.	
(6) CASING/LINER Casing Liner Dia + From To Gauge Stl Plste Wld Thrd		
<u> </u>		
	DEOENTE	
	NECEIVED	
Shoe X Inside Outside Other Location of shoe(s) 138	MAV: 9.1 core	
Temp casing Yes Dia From + To	MAY 31 2019	
(7) PERFORATIONS/SCREENS		
Perforations Method None	OWRD	
Screens Type Material	Date Started 03-22-2019 Completed 05-02-2019	
Perf/S Casing/ Screen Scrn/slot Slot # of Tele/		
creen Liner Dia From To width length slots pipe size	(unbonded) Water Well Constructor Certification	
	I certify that the work I performed on the construction, deepening, alteration, or	
	abandonment of this well is in compliance with Oregon water supply well	
	construction standards. Materials used and information reported above are true to the best of my knowledge and belief.	
 		
<u> </u>	License Number Date	
(8) WELL TESTS: Minimum testing time is 1 hour		
Pump Bailer Air Flowing Artesian	Signed	
	(bonded) Water Well Constructor Certification	
Yield gal/min Drawdown Drill stem/Pump depth Duration (hr)		
100-400	I accept responsibility for the construction, deepening, alteration, or abandonmen	
	work performed on this well during the construction dates reported above. All wor	
	performed during this time is in compliance with Oregon water supply we	
Temperature 56 °F Lab analysis Yes By	construction standards. This report is true to the best of my knowledge and belief.	
Water quality concerns? Yes (describe below) TDS amount 39.7 ppm	License Number 1688 Date 05-28-2018 Signed Atom 1, Hablel	
From To Description Amount Units	1 to	
	Signed Ham 11, Madel	
 	Contact Info (optional)	