MARI 69725 WESTERBERG DRILLING INC Revision Request 6/3/2021 STATE OF OREGON WELL I.D. LABEL# I 138741 PO BOX 1228 WATER SUPPLY WELL REPORT START CARD # 218317 MOLALLA, OR 97038 ORIGINAL LOG# (as required by ORS 537.765 & OAR 690-205-0210) (1) LAND OWNER Owner Well I.D. First Name Elizabeth Last Name Acevedo (9) LOCATION OF WELL (legal description) Company Come-N-Go County MARION Twp 5 S N/S Range 2 Address PO Box 749 __ E/W WM City Woodburn __ 1/4 of the NE _ 1/4 Tax Lot 200 State OR _ Zip <u>97071</u> Tax Map Number New Well Deepening Conversion (2) TYPE OF WORK or, DMS or DD Alteration (complete 2a & 10) __ or DMS or DD (2a) PRE-ALTERATION Street address of well Nearest address 13437 Portland Rd NE, Woodburn, OR 97071 <u>Material</u> Seal: (3) DRILL METHOD (10) STATIC WATER LEVEL Rotary Air Rotary Mud X Cable Auger Cable Mud SWL(psi) SWL(ft) Existing Well / Pre-Alteration Reverse Rotary Other Completed Well 02-25-2021 (4) PROPOSED USE ☑ Domestie ☐ Irrigation ☐ Community Flowing Artesian? Industrial/ Commercial Livestock Dewatering WATER BEARING ZONES Depth water was first found 18 Thermal Injection Other SWL Date Est Flow SWL(psi) + SWL(ft) From To (5) BORE HOLE CONSTRUCTION Special Standard (Attach copy) 02-25-2021 100+ 141 Depth of Completed Well 143 **BORE HOLE** SEAL sacky From Material To From <u>Amt</u> lbs 10 Λ 93 Bentonite 7 7 6 93 156 Calculated 3.5 Cement 93 54 (11) WELL LOG Calculated 24 Ground Elevation How was seal placed: Method □A □B ☒C □D From To XOther Bentonite Placed Dry Topsoil Backfill placed from 143 ft. to 156 ft. Material Pea Gravel **Brown Silt** 2 18 Filter pack from 94 ft. to 143 ft. Material CSS Grey Sandy Silt 18 57 Dense Grey Silt 57 70 Explosives used: Yes Type_ _ Amount Sand Grey Dirty 70 81 (5a) ABANDONMENT USING UNHYDRATED BENTONITE Clay Grey Stickey 81 93 **Pounds** Silt Grey Proposed Amount Actual Amount Pounds 93 97 Silt Grey Sandy 97 (6) CASING/LINER Casing Liner 90 Sand Grey/Black with some Gravel 99 106 From T_0 Gauge Gravel with Sand Medium Course 106 132 X 6 X 1.5 129.5 250 • Sand with Gravel Medium Grey XX 132 141 **●** 4 92.5 126 Sch40 Silty Grey Clay 141 149 E 141 143 Sch40 Sand Black with Clay Grey Layers 149 154 Clay Brown 154 156 Shoe Inside X Outside Other Location of shoe(s) 129.5 Temp casing X Yes Dia 10 From (7) PERFORATIONS/SCREENS Perforations Method Screens Type V-Wire Material Stainless Steel Date Started 02-09-2021 Completed 03-02-2021 Perf/S Casing/ Screen Scm/slot Slot # of Tele/ creen Liner (unbonded) Water Well Constructor Certification Dia width length pipe size Screen .040 4" PS I certify that the work I performed on the construction, deepening, alteration, or abandonment of this well is in compliance with Oregon water supply well construction standards. Materials used and information reported above are true to the best of my knowledge and belief. License Number (8) WELL TESTS: Minimum testing time is 1 hour Signed O Bailer Flowing Artesian Pump O Air Yield gal/min 75 Drawdown (bonded) Water Well Constructor Certification Drill stem/Pump depth Duration (hr) I accept responsibility for the construction, deepening, alteration, or abandonment work performed on this well during the construction dates reported above. All work

Signed

License Number

Contact Info (optional)

°F Lab analysis L. Yes By.

Yes (describe below) TDS amount 132

Description

Temperature 57

Water quality concerns?

performed during this time is in compliance with Oregon water supply well construction standards. This report is true to the best of my knowledge and belief.

Date 03-09-2021