NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report are to be filed with the
STATE ENGINEER, SALEM 10, OREGON within 30 days from the date of well completion.

State	Well No	7/2W-11	1	4
74-4-	D			,

/1\	***************************************	State Fermit No.			
(1) OWNER:		(11) WELL TESTS: Drawdown is amount water level is lowered below static level			
Name N. C. ADKINS Address RT 2 BOY 542		Was a pump test made? Yes \(\subseteq \text{No If yes, by whom? } \subseteq \text{DRILIER} \)			
THE N DOW OFF		Yield: gal/min. with ft. drawdov		hrs.	
SALEM, OREGON		<u>270 " I0 " " " " " " " " " " " " " " " " "</u>	II	,,	
(2) LOCATION OF WELL:		_'330 " I5 "	II	11	
County MARION Driller's we	Il number	BONEX Xest 400 gal./min. with 22 ft. drawdo	wn after	II hrs.	
	7 R. 2W W.M.	Artesian flow g.p.m. Date			
Bearing and distance from section or subdivis		Temperature of water Was a chemical analysis made? ☐ Yes ☐ No			
1600ft. No. E 23	300 ft. from Swar,11	(12) WELL LOG: Diameter of well below		·	
		- The second of well below (
	444	The state of the s			
		Formation: Describe by color, character, size of material and structure, and show thickness of aquifers and the kind and nature of the material in each stratum penetrated, with at least one entry for each change of formation.			
		MATERIAL	FROM	то	
(3) TYPE OF WORK (check):		TOP SOIL	0	4	
Well Deepening Recond	ditioning 🗌 Abandon 🖂	SANDY SILT	T		
bandonment, describe material and proced	ure in Item 12.	TAN CLAY & FINE GRAVET.	4	<u> 27 </u>	
(4) PROPOSED USE (check):	(E) MATRIE OF THEFT	GRAYISH CLAY	27	_35	
	(5) TYPE OF WELL:	BROWN SAND & GRAVEL	75 75	<u>75</u> 80	
Domestic Industrial Municipal	Rotary 🗌 Driven 🗌 Cable 🏗 Jetted 🗍	BROWN CLAY & GRAVET.		2/7	
Irrigation K Test Well Other	Dug 🗍 Bored 🗍	SAND & CRAVET	80 I00	100	
(6) CASING INSTALLED: Thr		BROWN CLAY & GRAVET.	I52	<u> 152</u>	
8	readed Welded K	YELLOW CLAY & GRAVEL	I57	<u> 157</u>	
"Diam. fromft. to		SAND & GRAVET.		<u> 167</u>	
"Diam. fromft. to		GRAY CLAY & GRAVET.	<u>I67</u>	<u> 172</u>	
11, 10	II. Gage	BLACK SAND & GRAVET.	172 Tan	<u> 177</u>	
(7) PERFORATIONS: Perf	orated? XYes No		T77	<u> 197</u>	
Type of perforator used MILLS					
Size of perforations in. by	in.				
64 perforations from 77					
perforations from	ft. toft.				
perforations from 170	ft. toft_				
perforations from	ft. toft.			·	
perforations from	ft. to ft.				
(8) SCREENS: Well screen inst	77 7 7 7 7	7.00			
Manufacturer's Name	alled 🗌 Yes 📉 No				
Mod					
Slot size Set from	ter No.			1	
Diam. Slot size Set from	it toft.		ULY IS	19	
	It. to ft.	Date well drilling machine moved off of well 19			
(9) CONSTRUCTION:		(13) PUMP:			
Well seal-Material used in seal PUDD]	LE CLAY & CEMENT				
Depth of seal 20 ft. Was a pac	ker used?	Manufacturer's Name Type: H.P.			
Diameter of well bore to bottom of seal	in,	н.г.			
Were any loose strata cemented off? \square Yes \square		Water Well Contractor's Certification:			
Was a drive shoe used? ☐ Yes ☐ No		This well was drilled under my jurisdiction a	nd this r	anort in	
Was well gravel packed? Yes No Size o	of gravel:	true to the best of my knowledge and belief.	110 0110 11	port is	
Gravel placed from ft. to	. It.	NIARE WILLAMETINE DOTT THE CO			
Did any strata contain unusable water? Yes	□ No	NAME WILLAMETTE DRILLING CO (Person, firm or corporation) (Type or print)			
Type of water? Depth of str		Address RT 2 BOX 276 SALEM, OREGON			
Method of sealing strata off	jacy a				
(10) WATER LEVELS:		Drilling Machine Death of Liversey 10B NO752			
Static level 55 ft. below land s	urfoce Data	[Signed](Water Well Contractor)			
Artesian pressure lbs. per square		(" and " only actor)			
yer square	- mon Date	Contractor's License No. 2 Deta TIIT V	TO		