STATE OF OREGON WATER SUPPLY WELL REPORT (as required by OPS 537 765 & OAR 690-205-0210)

MARI 69905

WELL I.D. LABEL# L 132871

START CARD # 1049510

ORIGINAL LOG #

(as required by ORS 537.765 & OAR 690-205-0210)	6/11/2021	ORIGINAL LOG#			
(1) LAND OWNER Owner Well I.D.			<u> </u>		
First Name JEFF Last Name BIZON	(9) LOCA	(9) LOCATION OF WELL (legal description)			
Company STAFFER FARM INC.	I ' '	ION Twp 4.00 S N/S	-	W E/W WM	
Address 13851 STAUFFER RD. NE City HÜBBARD State OR Zip 97032	- Sec <u>35</u>	NW 1/4 of the NW	1/4 Tax Lot 600)	
(2) TYPE OF WORK New Well Deepening Conversion	Tax Map Nu	nber " or"	Lot		
Alteration (complete 2a & 10) Abandonment(compl	ete 5a) Lat	° " or		DMS or DD	
(2a) PRE-ALTERATION	Long	o or	. 11	_ DMS or DD	
Dia + From To Gauge Stl Plstc Wld Thrd Casing:		SKEY HILL RD. NE	irest address		
Material From To Amt sacks/lbs	HUBBARD				
Seal:	Певына	OK .			
(3) DRILL METHOD	(10) STAT	TIC WATER LEVEL			
Rotary Air Rotary Mud Cable Auger Cable Mud	Existing	Well / Pre-Alteration Date	SWL(psi) +	SWL(ft)	
Reverse Rotary Other	Complet		++	59.6	
(4) PROPOSED USE Domestic X Irrigation Community		Flowing Artesian?	Dry Hole?	57.0	
Industrial/ Commercial Livestock Dewatering	WATER BEA	RING ZONES Depth war	ter was first found	117.00	
Thermal Injection Other	SWL Date		Flow SWL(psi)		
(5) BORE HOLE CONSTRUCTION Special Standard (Attac	ch copy) 10/30/202				
Depth of Completed Well 247.40 ft.	11/9/2020		80	58	
BORE HOLE SEAL	sacks/ 11/11/202		250	59	
Dia From To Material From To Amt	lbs				
20 0 38 Bentonite Chips 0 38 2350 16 38 292 Calculated 2350					
10 38 292 Calculated 2330					
Calculated	(11) WEL	L LOG Ground Elevation	1		
How was seal placed: Method A B C D E		Material	From	То	
X Other OAR 690-210-0340	Top soil	1 1	0	1	
Backfill placed from 247.4 ft. to 292 ft. Material CEMENT	Clay, brown,		7	7 13	
Filter pack from 195 ft. to 200 ft. Material GRAVEL Size 6/9	Clay, brown,		13	18	
Explosives used: Yes Type Amount	Clay, brown,		18	36	
(5a) ABANDONMENT USING UNHYDRATED BENTONITE		llowish brown,	36	42	
Proposed Amount Actual Amount	Clay, greenis		42 61	70	
(6) CASING/LINER Casing Liner Dia + From To Gauge Stl Plstc Wld	Silt and sand	, dark gray, hard	70	78	
8 1 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2	Silt, dark bro		78	82	
	Clay, gray, h		82	84	
	Clay, dark gr	ay, soft k gray silt, hard	84 89	89 103	
		ay, hard, sticky	103	103	
		eenish gray, hard	108	114	
Shoe Inside Outside Other Location of shoe(s) 194.3		vel, claybound	114	117	
Temp casing Yes Dia From + To		and, black, loose eenish gray, med, sticky	117 128	128 144	
(7) PERFORATIONS/SCREENS		eenish gray, hard, sticky	144	156	
Perforations Method			'		
Screens Type v wire Material Stainless Perf/ Casing/ Screen Scrn/slot Slot # of	Tele/ Date Starte	ed <u>10/21/2020</u> Comp	oleted <u>1/20/2021</u>		
Screen Liner Dia From To width length slots pi	pe size (unbonded)	Water Well Constructor Certific			
Screen Casing 12 195 209.3 .065		t the work I performed on the cont of this well is in compliance			
Screen Casing 12 209.3 226.5 .25		standards. Materials used and inf			
		y knowledge and belief.	1		
	License Nun	nber Da	ite		
(8) WELL TESTS: Minimum testing time is 1 hour					
(Pump Bailer Air Flowing Artesi	ian Signed —				
Yield gal/min Drawdown Drill stem/Pump depth Duration (hr)	(bonded) W	ater Well Constructor Certificati	ion		
1075 107 186 5		onsibility for the construction, de			
		ned on this well during the construc			
		uring this time is in compliance standards. This report is true to the			
Temperature 54 °F Lab analysis Yes By		_	-	abe and benefic.	
	<u>ppm</u> License Nun	Da Da	te 6/11/2021		
	Signed IV	AN GROSSEN (E-filed)			
		(optional)			

		-	 _	-	_
L	132871				
ŧ	1049510				
į					

continuation page	6/11/2021 ORIGINAL LOG #	
2a) PRE-ALTERATION	Water Quality Concerns	•
Dia + From To Gauge Stl Plstc Wld Thrd		Amount Units
Material From To Amt sacks/lbs		
5) BORE HOLE CONSTRUCTION	(10) STATIC WATER LEVEL	
DODE HOLE SEAL	SWL Date From To Est Flow SWL((psi) + SWL(ft)
Dia From To Material From To Amt	icks/	
Calculated		
Calculated	_	
Calculated		- $ $ $+$ $ $
Calculated		-
FILTER PACK	(11) WELL LOG	
From To Material Size	Material From	m To
200 247 GRAVEL 1/4"		56 165
	Dark green and gray silt, bedded, hard 1	65 167
6) CASING/LINER		67 174 74 183
	Silt, greenish gray, hard, dry 1	83 185
Casing Liner Dia + From To Gauge Stl Plstc Wld Th	Sitt, gray, nard, dry	85 187 87 195
		95 201
	Sand and gravel, black 2	01 226
		26 228 28 256
	Clay, light brown, hard, sticky 2	56 262
	278 27 7 2	.62 <u>267</u> .67 <u>292</u>
	J	
7) PERFORATIONS/SCREENS		
	Tele/	
	pe size	
	Comments/Remarks	
(9) WELL TESTS. Minimum testing time is 1 hours	Bottom plate 247.4'	
(8) WELL TESTS: Minimum testing time is 1 hour	Lift bar 1.5' from bottom	
Yield gal/min Drawdown Drill stem/Pump depth Duration (hr)		
	1 1	l