NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report are to be filed with the

STATE ENGINEER, SALEM, OREGON within 30 days from the date of well completion.

STATE OF OREGON NOV 2 2 1972 State WATER WELL

(Please type of TATE ENGINEER

(Do not write above the IM) EM OREGO State Permit No.

(1) OWNER:	(10) LOCATION OF WELL:
Name Clarence Simmons	County Marion Driller's well number
Address Rt.e. 2, Silwerton, Ore. 97381	1/4 1/4 Section T. R. W.M.
	Bearing and distance from section or subdivision corner
(2) TYPE OF WORK (check):	Approx. 2500' W. 1750' N.of S. E. cor
New Well ☐ Deepening K Reconditioning ☐ Abandon ☐	of sec 12. T.78. R.2W.
If abandonment, describe material and procedure in Item 12.	
	(11) WATER LEVEL: Completed well.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found ft.
Rotary 🖰 Driven 🗌 Domestic 🗆 Industrial 🗆 Municipal 🗍	Static level 37 ft. below land surface. Date 4 20-72
Dug ☐ Bored ☐ Irrigation ▼ Test Well ☐ Other ☐	Artesian pressure lbs. per square inch. Date
CASING INSTALLED: Threaded Welded X 8 " Diam. from 139 ft. to 244 6 ft. Gage 250 10 " Diam. from ft. to 145 ft. Gage 250 ft. Origa ft. Gage 250 PERFORATIONS: Perforated 15 Yes 2 No.	(12) WELL LOG: Diameter of well below casing
Type of perforator used	MATERIAL From To SWL
	med. sand andgravel grey140 143 Clay dark brn. med. hd. 143 152
perforations fromft. toft.	clay gray hard 152 155
perforations fromft. toft.	clay grey sticky med. hd155 198
perforations from ft. to ft.	clay reddish brn.soft 198 233
(7) SCREENS: Well screen installed? Yes No	Tufatione firm greyish brn233 246
Manufacturer's Name	Weathered basaalt med hd 246.251
TypeModel No	lava red med. hd. 251 263
Diam Slot size Set from ft. to ft.	weathered basaalt brn. md. 263 281 w.B.
Diam Slot_size ft. to ft.	hassalt grey hd. 28% 338
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	basalt porous gy med hd 338 346 w.B
Was a pump test made? X Yes ☐ No If yes, by whom? OWNOY	
Yield: 120 gal./min. with 98 ft. drawdown after 15 min	9
ir 150 " 300 " 8 hrs".	
with original water cased off, & after Top	139'alog sing was cut off
Bailer test gal./min. with ft. drawdown after hrs.	
	The yield about doubled with
Artesian flow g.p.m.	
perature of water 🔏 Depth artesian flow encountered ft.	Work started - 19-72 1972 Completed 5-15-72 19 72
(9) CONSTRUCTION:	Date well drilling machine moved off of well 5 72 19 72
Well seal-Material used	Drilling Machine Operator's Certification: This well was constructed under my direct supervision. Materials used and information reported above are true to my
Diameter of well bore to bottom of seal	best knowledge and belief.
Diameter of well bore below seal in.	[Signed] Taul J. Stadeli Date 1/-4, 1972
Number of sacks of cement used in well seal sacks	(Drilling Machine Operator)
Number of sacks of bentonite used in well seal sacks	Drilling Machine Operator's License No
Brand name of bentonite	Water Well Contractor's Cartification
Number of pounds of bentonite per 100 gallons	Water Well Contractor's Certification:
of waterlbs./100 gals.	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Was a drive shoe used? 🖺 Yes 🗌 No Plugs Size: location ft.	Name R. Stadelix Sons, Inc.
Did any strata contain unusable water? 🗌 Yes 🕱 No	(Person, firm or corporation) (Type or print)
Type of water? depth of strata	Address Ate 3, Boy 169, Selverton, atl.
Method of sealing strata off	Soul Q St. Isl:
Was well gravel packed? ☐ Yes 🖔 No Size of gravel:	[Signed] (Water Well Contractor)
	Contractor's License No. 296 Date 1/-4 , 1972
Gravel placed from ft. to ft.	Contractor's License No. W. Date Date 19.