## NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the AUG 1 1 97 STATE OF OREGON

State Permit No.

STATE ENGINEER, SALEM, OREGON 97810 [ [Please type or print) within 30 days from the date of well completion. SALEM OF (Do not write above this line)

tate Well No	12/2M-12 0	
late Wen 110.	1	•

(1) OWNER: Name Pratum School D/57 # 50	(10) LOCATION OF WELL:  County Mar ion Driller's well num	nber	
Address %. WILLIS . GOFBEL CLERK 9895. SUNNYWE	N.W. 14 S.E. 14 Section 13 T.S. I	R. 2. W. W.M.	
SALEM, OREG.	bearing and distance from section or subdivision	n corner	
(2) TYPE OF WORK (check):	Doming and and		
New Well			
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed we	11.	
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found	85 st.	
	Static level 45 ft. below land su	urface. Date 8/2/72	
Rotary	Static level 40 ft. below land su  Artesian pressure lbs. per square		
(5) CASING INSTALLED: Threaded □ Welded ♣ 6	(12) WELL LOG: Diameter of well be ft. Depth of comple formation: Describe color, texture, grain size at and show thickness and nature of each stratum with at least one entry for each change of formation position of Static Water Level and indicate prince	ted well 177  ft.  nd structure of materials;  a and aquifer penetrated,  ion. Report each change in	
Type of perforator used	MATĒRIAL	From To SWL	
Size of perforations in. by in.	Top soil brn.	0 1	
perforations from ft. to ft.	Ila y brn.	1 35	
perforations fromft. toft.	Clay sandy brn.	3 5 45	
perforations from ft. to ft.	Fine Conglomerate brn.	4 5 60	
	Clay b rn.	7 0 89	
(7) SCREENS: Well screen installed?   Yes To No	Med Conglom brn		
Manufacturer's Name	Glay brn.	89 130	
Type Model No	II - abar 6roj	13 0 177	
<del> </del>	H. broken basalt, green& brn.	177 313	
Diam. Slot size Set from ft. to ft.	seams W.B.	111191	
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	*		
Was a pump test made?   Yes Y No If yes, by whom?	Bavelled back to 177		
eld: gal./min. with ft. drawdown after hrs.			
, n			
" " "			
Air 37 gal./min. with ft. drawdown after hrs.			
Datter tess			
Artesian flow g.p.m.	Work started 7/28/72 19 Complete	ed 8/2/72 <sub>19</sub>	
imperature of water Depth artesian flow encountered ft.	Date well drilling machine moved off of well	8/2/72 19	
(9) CONSTRUCTION:			
Well seal—Material used  Well sealed from land surface to 136  Diameter of well bore to bottom of seal in.  Number of sacks of cement used in well seal sacks	Drilling Machine Operator's Certification:  This well was constructed under my direct supervision.  Materials used and information reported above are true to my best knowledge and belief.  [Signed Machine Operator)  Drilling Machine Operator's License No.		
Number of sacks of bentonite used in well sealsacks	Drining Machine Operator's License No.		
Brand name of bentonite National	Water Well Contractor's Certification:		
Number of pounds of bentonite per 100 gallons of water 100 gals.	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.		
Was a drive shoe used?   ✓ Yes ☐ No Plugs Size: location ft.	P S tadeli & Sons Inc.		
Did any strata contain unusable water?   Yes  No	(Person, firm or corporation) (Type or print)		
	Address Silverton, Oreg.		
Type of water? depth of strata  Method of sealing strata off	[Signed] Joul A. Stadeli		
Was well gravel packed? ☐ Yes X No Size of gravel:	(Water Well Cont		
Gravel placed from ft. to ft.	Contractor's License No. 296 Date	8/7 /72 <sub>19</sub>	
Graver placed from			