NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report are to be filed with the

WATER WELL REPORTE | V E D

STATE OF OREGON

State We

	7	1-		
ell No.	151	Z ()	<u>) </u>	
	7			

STATE ENGINEER, SALEM, OREGON, 973 within 30 days from the date of well completion.

(Please type or print) FEB 21977

STATE OF OREGON	0.4077				- 1	
* (Please type or print) FEB	13 1977	 .	·-		•	
(Do not write above this line) ES			Permit	No.	***************************************	
7. J. J. Land						 _

(1) OWNER:	(10) LOCATION OF WELL:	
and the second s		nber 2003
Name John Hay	IRLLUII	
Address 7514 Sunnyview Rd. NE Salem, Cregon 97	3 6 3 ¼ ¼ Section 1 5 T. Z. 7 S	₩
(a) myne of work (shock).	Bearing and distance from section or subdivision	n corner
(2) TYPE OF WORK (check):		
New Well ☐ Deepening ☐ Reconditioning ☐ Abandon ☐		
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed we	:II.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found	52 ft
Rotary Driven Domestic Industrial Municipal		rface. Date 1/18/77
Cable Jetted Domestic Industrial Industrial		
Dug ☐ Bored ☐ Irrigation M Test Well ☐ Other ☐	Artesian pressure lbs. per square	inch. Date
CASING INSTALLED: Threaded Welded	(12) WELL LOG: Diameter of well b	alama aadma
10 " Diam. from top ft. to 150 ft. Gage •250		elow casing eted well 150 for
	Formation: Describe color, texture, grain size a and show thickness and nature of each stratum	nd structure of materials and aquifer penetrated
	with at least one entry for each change of format	ion. Report each change i
PERFORATIONS: Perforated? Types No.	position of Static Water Level and indicate princ	ipal water-bearing strate
Type of perforator used Mills Knife	MATERIAL	From To SWL
Size of perforations 7/16 in. by 2 3/4 in.	Topsoil	0 1
1060 perforations from 55 ft. to 149 ft.	Yellow Clay	1 52
perforations from ft. to ft.	Brown sand and gravel	52 80
perforations from ft. to ft.	Cemented Brown sand and Gravel	80 150
portorativals from		
(7) SCREENS: Well screen installed? Yes No		
Manufacturer's Name		
Type Model No		
Diam. Slot size Set from ft. to ft.		
Diam. Slot size Set from ft. to ft.		
(2) WELL TESTS. Drawdown is amount water level is		
(8) WELL TESTS: Drawdown is amount water level is lowered below static level		
Was a pump test made? Yes \(\) No If yes, by whom driller		
viold: 300 gal./min. with 38 ft. drawdown after 1 hrs.		
500 " 58 " 1 "		
" " "		
Bailer test gal./min. with ft. drawdown after hrs.		
Artesian flow g.p.m.		
iperature of water 53 Depth artesian flow encountered ft.	Work started 12/17/76 19 Complete	ed 1/18/76 19
(9) CONSTRUCTION:	Date well drilling machine moved off of well	1/18/77 19
Doubland Comout	Drilling Machine Operator's Certification:	
17 0.12 2001 2.2000.202 0.000	This well was constructed under my	direct supervision
Well sealed from land surface to	Materials used and information reported best knowledge and belief.	above are true to m
		Date 1/18/76, 19
Diameter of well bore below seal	(Drilling Machine Operator)	
	Drilling Machine Operator's License No.	536
Number of sacks of bentonite used in well seal sacks		
Brand name of bentonite	Water Well Contractor's Certification:	
Number of pounds of bentonite per 100 gallons of waterlbs./100 gals.	This well was drilled under my jurisd	ction and this report
of water	true to the best of my knowledge and bel	ICT.
	Name Willamette Drilling Co. (Person, firm or corporation)	(Type or print)
Did any strata contain unusable water? Yes No	Address 1450 Barnick Rd. NE Sale	R.
Type of water? depth of strata	Address	
Method of sealing strata off	[Signed] Wallas T Days	
Was well gravel packed? Yes No Size of gravel:	(Water Well Conta	•
Gravel placed from ft. to ft.	Contractor's License No. 561 Date 1	/1 8 /77 , 19
		CTD+AE0E0 1