WATER WELL REPORT

MAY 7 1981

RECEIVED

State Permit No.

STATE OF OREGON WATER RESOURCES DEPT SALEM, OREGON

(1) OWNER:	(10) LOCATION OF WELL:	
Name Hatlan C. Selby	County Marion Driller's well number	
Address 3195 Cordon Rd. N.E.	N.E. 1/4 N.W. 1/4 Section 17- T. 7 S. R. 2	W • W.M
City Salem, Oregon 97303 State		<u>subdivision</u>
(2) TYPE OF WORK (check):	Address at well location: Same as in item # 1.	
New Well □ Deepening □ Reconditioning X Abandon □	(11) WATER LEVEL: Completed well.	
If abandonment, describe material and procedure in Item 12.		
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found Orig Static level 8 ft. below land surfa	fi ace. Date 4/10/8
Rotary Air Driven Domestic & Industrial Municipal	Artesian pressure lbs. per square	
Bothary Mud Dug Irrigation Test Well Other Thermal: Withdrawal Reinjection	(12) WELL LOG: Diameter of well below casing	^
) CASING INSTALLED: Steel & Plastic	Depth drilled 0 ft. Depth of complete	
Threaded □ Welded 2 orig. 6 Diam. from 2 - ft. to 92 1/2 ft. Gauge 250 now-6 "Diam. from 1+ ft. to 92 1/2 ft. Gauge 250	Formation: Describe color, texture, grain size and structure of thickness and nature of each stratum and aquifer penetrated, we for each change of formation. Report each change in position of and indicate principal water-bearing strata.	rith at last one entry
LINER INSTALLED:	MATERIAL From	To SWL
XX "Diam. from ft. to ft. Gauge	Med. sand & Gravel at bottom	
	of casing	921/2
(6) PERFORATIONS: Perforated? ☐ Yes X No Type of perforator used		
Size of perforations in. by in.		
perforations from		
perforations from		
perforations from		
	V 23 3 20 0 6 6 0	-
(7) SCREENS: Well screen installed? Yes XNo Manufacturer's Name	We welded 34" of 6" casing on	
Type	top to bring it up to 1' above	
Diam. Slot Size Set from ft. to ft.	the surface.	
Diam. Slot Size Set from ft. to ft.		
(8) WELL TESTS: Drawdown is amount water level is lowered below static level Drillers &		
a pump test made? Yes No If yes, by whom? Pumpmen.		
d: 15 gal./min. with 12 ft. drawdown after 1 hrs.		
" " "		
Air test gal./min. with drill stem at ft. hrs.		
Bailer test 35 gal./min. with 22 ft. drawdown after 1 hrs.		
sian flow g.p.m.		
.nperature of water XX Depth artesian flow encountered ft.	Work started 4/6/81 19 Completed 4/1	10/81 19
(9) CONSTRUCTION: Special standards: Yes No X	Date well drilling machine moved off of well 4/1	0/81 19
Well seal—Material used Original	Drilling Machine Operator's Certification:	•
Well sealed from land surface to	This well was constructed under my direct supervisi	ion. Materials use
Diameter of well bore to bottom of seal in.	and information reported above are true to my jest know	wledge and belief. e 4-36 19 8 /
Diameter of well bore below sealin.	(Drilling Machine Operator)	e 7
Number of sacks of cement used in well seal sacks	Drilling Machine Operator's License No	
How was cement grout placed?	Water Well Contractor's Certification:	
	This well was drilled under my jurisdiction and this report is true to	
Was pump installed? Yes Type Sub. HP 3/4 Depth 67 ft.	the best of my knowledge and belief.	
Was a drive shoe used? ☐ Yes ☐ No Plugs	Name R.Stadeli & Sons, Inc.	(Type or print)
Did any strata contain unusable water?	Address 11364 Evrgrn.Rd.N.E. Silvrtn.O)r. 97381
Type of Water? depth of strata	Q-16 2+ 1-1.	
Method of sealing strata off	[Signed] (Water Well Contractor)	
Was well gravel packed? Tyes I No Size of gravel: 3/4."to3/	Contractor's License No. 296 Date 4/30/81	19
Gravel placed from		