WATER WELL REPORT

AS SUNTED TO MARI



State Permit No.	7253
Duave I elillicito.	

(1) OWNER:	(10) LOCATION OF WELL:	
Name Dan Stauffer	County Marion Driller's well number S-1	
Address 1660 Hamdon Lane N.E.	SE 4NE 4 Section 20 T.7S R. 2W	W.M.
City Salem Oregon State Or.	Tax Lot # Lot Blk Subdivision	
	Address at well location: 1660 Hamdon Lane	
(2) TYPE OF WORK (check):		
New Well Deepening □ Reconditioning □ Abandon □	(11) WATER LEVEL: Completed well.	
If abandonment, describe material and procedure in Item 12.	Depth at which water was first found 49	£
TYPE OF WELL: (4) PROPOSED USE (check):	Static level 26 ft. below land surface. Date 1	0-3-8 0
Rosary Air 🕱 Driven 🗆 Domestic 🚨 Industrial 🗆 Municipal 🗆	Artesian pressure lbs. per square inch. Date	
Rotary Mud	(12) WELL LOG: Diameter of well below casing10	
	Depth drilled 177 ft. Depth of completed well 17	
CASING INSTALLED: Steel to Plastic Welded Threaded	Formation: Describe color, texture, grain size and structure of materials; thickness and nature of each stratum and aquifer penetrated, with at least for each change of formation. Report each change in position of Static Wa and indicate principal water-bearing strata.	and show one entry
LINER INSTALLED:	MATERIAL From To	SWL
	Soil brn 0 2	
	Clay med brn 2 26	
(6) PERFORATIONS: Perforated? Zero Yes □ No Type of perforator used Perf Hawk		
Size of perforations $3/8$ in. by $1\frac{1}{2}$ in.	Clay med grey 26 44 Sand blk gravel med brn 44 62	
3521 perforations from 100 ft. to 155 ft.	Clay med blue 62 73	
1326 perforations from 1.55 ft. to 1.73 ft.	Gravel med-lge sand brn 73 160	
perforations from ft. toft.	Gravel lge lite sand br160 177	
(7) SCREENS: Well screen installed? Yes X No		
Manufacturer's Name		
Type Model No. Diam. Slot Size Set from ft. to ft.		
Diam. Slot Size Set from It. to It. Diam. Slot Size Set from ft. to It.		
Drawdown is amount water level is lowered		
WELL TESTS: below static level	REUSAULU	
[™] as a pump test made? ☐ Yes 🛂 No If yes, by whom?	OCT 1 3 1980	
eld: gal./min. with ft. drawdown after hrs.		
" "	WATER RESOURCES DEPT	
est 400 gal./min. with drill stem at 175 ft. 2½ hrs.	SALEM, OREGON	
bester test gal./min. with ft. drawdown after hrs.		
tesian flow g.p.m.		
Depth artesian flow encountered ft.	Work started 9-29-80 19 Completed 10-3	19 0
(9) CONSTRUCTION: Special standards: Yes \(\text{No } \text{ No } \text{ \text{\$\$\text{\$\exititt{\$\text{\$\text{\$\text{\$\text{\$\text{\$\texi\\$\$\}}\$}}}}}}}}}} \text{\$\text{\$\text{\$\text{\$\text{\$\text{\$\text{\$\text{\$\	Date well drilling machine moved off of well 10-3	19 80
Well seal—Material used Cement	Drilling Machine Operator's Certification:	
Well sealed from land surface to	This well was constructed under my direct supervision. Materi	
Diameter of well bore to bottom of seal15in.	and information reported pove and the to my best knowledge and [Signed] Datel 09	
Diameter of well bore below seal	Drilling Machine Operator)	, 19.0.0.
Number of sacks of cement used in well seal	Drilling Machine Operator's License No	
How was cement grout placed?	Water Well Contractor's Certification:	
	This well was drilled under my jurisdiction and this report is	s true to
Was pump installed? NO	the best of my knowledge and belief.	
Was a drive shoe used? Mayes □ No Plugs Size: location ft.	Name West Coast Drilling Co. Inc. (Person, firm or corporation)	wint)
Did any strata contain unusable water? 🗆 Yes 🐰 No	Address 220 Academy St. Mt. Argel Or.	
Type of Water? depth of strata	1 hallon & Toll	le
Method of sealing strata off	[Signed] (Water Well Contractor)	
Was well gravel packed? ☐ Yes ☐ No Size of gravel:	Contractor's License No. 519 Date 10-9	, ₁₉ 80
Gravel placed from ft. to ft.		