TA 1R1.7.1

NOTICE TO WATER WELL CONTRACTOR ET The original and first form of this report are to the DEC 10 1065 or this report are to the DEC 10 1965 TER WELL SEPORT ENGINEER STATE ENGINEER, OREGON 97310 STATE OF OREGON LEM OREGON 97310 OF Well completion of State Permit No. ....

1) OWNER:	(11) WELL TESTS: Drawdown is another lowered below static	levei	
Name Steve Piccardo	Was a pump test made? 🗷 Yes 📋 No If yes, by wh	om? dr1.	
Address	Yield: 80 gal./min. with 23 ft. drawd	own after	4 hrs.
Hubbard, Oregon	" 150 " 35 " " 220 " 48 "		2 "
2) LOCATION OF WELL:		down after	<del></del> _
County Karian Driller's well number	Daller test San, to a	down arter	- 1113.
14 14 Section 23 T. 4S R. 1W W.M.	Artesian flow g.p.m. Date  Temperature of water Was a chemical analysi	s made? [] '	Yes 🕱 No
Bearing and distance from section or subdivision corner		7	0
Scaring and distance from socious s	(12) WELL LOG: Diameter of well below	casing	
	Depth drilled 210 ft. Depth of completed		210 ft.
	Formation: Describe by color, character, size of mate show thickness of aquifers and the kind and nature c stratum penetrated, with at least one entry for each	rial and stru of the mater	cture, and ial in each
	stratum penetrated, with at least one entry for each	change of	formation.
	MATERIAL	FROM	то
(3) TYPE OF WORK (check):	Surface	0	3
Well ■ Deepening □ Reconditioning □ Abandon □	Brown sandy clay	3	88
andonment, describe material and procedure in Item 12.	Broken sand & small gravel	88	93
	Blue clay	93	99
(4) PROPOSED USE (check): (5) TYPE OF WELL:	Red sand	-	107
Domestic   Industrial   Municipal   Rotary   Driven   Cable <b>Z</b> Jetted	Broken sand & gravel		116
Irrigation I Test Well   Other   Dug   Bored	Blue sandy clay		13216"
	Broken gravel & clay	13216"	1
(6) CASING INSTALLED: Threaded  Welded	Gravel	138	140
10" Diam. from	Blue sandy clay	140	147
ft. Gage ft. Gage	Sand	147	149
ft. Gageft.	Grey clay	149	165
(7) PERFORATIONS: Perforated? A Yes No	Sand (no water)	165	167
Type of perforator used Millknife	Clay	167	196
7	Sand	196	200
Size of perforations 3/8 in. by 1 in. 4/0 perforations from 4/2 ft. to 4/2 ft.	Blue clay	200	210
35 perforations from 138 ft. to 140 ft.			
perforations from ft. to ft.			
perforations from ft. to ft.			
perforations from ft. to ft.			
(8) SCREENS: Well screen installed? ☐ Yes ▼ No			
Manufacturer's Name			<u> </u>
Model No.			
Drain Slot size Set from ft. to ft.	Work started Dee Nov 5 1965 Completed	Dec 2	1965
Diam. Slot size Set from ft. to ft.	Date well drilling machine moved off of well	Dec 2	<u> 1865</u>
(9) CONSTRUCTION:	(13) PUMP:		
Puddled Mud	Manufacturer's Name		
Well seal—Material used in seal Puddled Mud  Depth of seal 20 ft. Was a packer used? no	Type:	H P	***************************************
Diameter of well bore to bottom of seal	1300	4414 1	
Were any loose strata cemented off? Yes No Depth	Water Well Contractor's Certification:		
<u> </u>	This well was drilled under my jurisdiction	n and this	s report is
Was a drive shoe used? ☐ Yes TNO Size of gravel:	true to the best of my knowledge and belief.		
Trab West States Passing III	* 1 M		
Gravel placed fromftft.	NAME John Truman Miller (Person, firm or corporation)	(Type or prin	1t)
Did any strata contain unusable water? ☐ Yes ♠ No  Type of water? depth of strata	Address P 0 Box 42 Hubbard	i, Oreg	on
	·	_	
Method of sealing strata off	Drilling Machine Operator's License No	26	
(10) WATER LEVELS:	[Signed] John Miller		
Static level 65 ft. below land surface Date 12/2/65	(Water Well Contract	or)	
Artesian pressure lbs. per square inch Date	Contractor's License No. 277 Date Dece	mban.4.	, 1965
	ייים אודיר אייים איי	-neT	