

NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report are to be filed with the

RECEIVED WATER WELL REPORT

WATER RESOURCES DEPARTMENT,
SALEM, OREGON 97310
within 30 days from the date
of well completion.

OCT 9 1978 STATE OF OREGON
(Please type or print)

WATER RESOURCES DEPT.
SALEM, OREGON

74154
M. I. WALDROF

State Well No. 75/2w20ac
State Permit No.

(1) OWNER:

Name R.T. Mosman
Address 5999 Culver Dr. S.E.
Salem, Oregon

(2) TYPE OF WORK (check):

New Well Deepening Reconditioning Abandon
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary Driven
Cable Jetted
Dug Bored

(4) PROPOSED USE (check):

Domestic Industrial Municipal
Irrigation Test Well Other

CASING INSTALLED:

Threaded Welded
5" Diam. from +1 ft. to 109 ft. Gage .250
" Diam. from ft. to ft. Gage
" Diam. from ft. to ft. Gage

PERFORATIONS:

Perforated? Yes No.
Type of perforator used Mill's Knife
Size of perforations 3/8 in. by 3 in.
30 perforations from 95 ft. to 99 ft.
216 perforations from 50 ft. to 85 ft.
perforations from ft. to ft.

(7) SCREENS:

Well screen installed? Yes No

Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS:

Drawdown is amount water level is lowered below static level

Was a pump test made? Yes No If yes, by whom?
Yield: gal./min. with ft. drawdown after hrs.
" " " " " "
" " " " " "
Bailer test 50 gal./min. with 9 ft. drawdown after 1 hrs.
Artesian flow g.p.m.
perature of water Depth artesian flow encountered ft.

(9) CONSTRUCTION:

Well seal—Material used portland cement
Well sealed from land surface to 29 ft.
Diameter of well bore to bottom of seal 12 in.
Diameter of well bore below seal 8 in.
Number of sacks of cement used in well seal 21 sacks
How was cement grout placed? air grout pump

Was a drive shoe used? Yes No Plugs Size: location ft.
Did any strata contain unusable water? Yes No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? Yes No Size of gravel:
Gravel placed from ft. to ft.

(10) LOCATION OF WELL:

County Marion Driller's well number
SW 1/4 NE 1/4 Section 20 T. 7S R. 2W W.M.
Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.

Depth at which water was first found 40 ft.
Static level 18 ft. below land surface. Date 9-10-78
Artesian pressure lbs. per square inch. Date

(12) WELL LOG:

Diameter of well below casing 0"
Depth drilled 109 ft. Depth of completed well 109 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
Brown clay	0'	24'	
Blue clay	24'	40'	
Black fine-medium sand + small-large gravel			
Black sand + gravel with some blue clay	40'	82'	18'
Brown fine-medium sand + sm-lrg. gravel with occasional cemented	82'	90'	
RTERS	90'	109'	18'

Work started Sept. 5 1978 Completed Sept. 20 1978
Date well drilling machine moved off of well Sept. 21 1978

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.
[Signed] Michael Waldroff Date 9-21, 1978
(Drilling Machine Operator)
Drilling Machine Operator's License No. 873

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Name MILLER & WEST DRILLING
(Person, firm or corporation) (Type or print)
Address 5875 Gaffin R.D. SE.
[Signed] Michael Waldroff
(Water Well Contractor)
Contractor's License No. 633 Date 9-21, 1978