The original and first of this report are to filed with the STATE ENGINEER, SALEM STEAM TEST ENGINEER Please type or print) within 30 days from the late TEST ENGINEER Please type or print) of well completion. SALEM. OREGONO not write above this line)

State Permit No.

	0000		
(1) OWNER;	(10) ISOCATION OF WELL:		
Name Mily & Wilson	County Marion Driller's well number		
Address / 260 Bonols Ro. M. E. Salem	14 14 Section 20 T. 75	R. 2 4/	W.M.
(a) mype of more (1.1.)	Bearing and distance from section or subdivision		77,472.
(2) TYPE OF WORK (check):			
New Well Deepening Reconditioning Abandon			
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed we	.11	
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 38		
Rotary Driven Domestic Industrial Municipal	Static level 22 ft. below land surface. Date 10-29		
Cable	Artesian pressure lbs. per square inch. Date		
CACTAGO TATOMAT I TO	ins. per square	men. Date	
) CASING INSTALLED: Threaded Welded	(12) WELL LOG: Diameter of well below casing		
8 "Diam from t / tt to // 8 ft Gage .250	Depth drilled //8 ft. Depth of completed well //8 ft.		
ft. Gage ft. Gage	Formation: Describe color, texture, grain size an		
" Diam, from ft. to ft. Gage	and show thickness and nature of each stratum	and aquifer ne	enetrated.
) PERFORATIONS: Perforated? Fyes No.	with at least one entry for each change of formation position of Static Water Level and indicate principal principal states.	on. Report each	chanae in
Type of perforator used $\mathcal{M}_1//\mathcal{S}$	MATERIAL		,
Size of perforations 3/8 in. by 2-2 in.	A A	From To	SWL
350	Larown Clay	0 20	
10	30 1 1 1 11		
perforations from ft. to ft.	Deut Handy Clay	20 38	
	Sand and Stravel	38 48	
(7) SCREENS: Well screen installed? Yes No			
Manufacturer's Name	Brown Clark	48 52	
Type Model No		,,, ,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	
Diam. Slot size Set from ft. to ft.	Blue May	52 58	
Diam. Slot size Set from ft. to ft.			
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	Brown Sand	58 73	
Was a pump test made? Yes No If yes, by whom?	Small to Lang Strange	73 81	
Yield: gal./min. with ft. drawdown after hrs.			
" " "	Comented Granel	81 118	
" " " "			
Bailer test 65 gal./min. with 6 ft. drawdown after hrs			
The state of the s			
Artesian flow g.p.m.			
nperature of water Depth artesian flow encountered ft.	Work started /8 - 22 19 7/Completed	16-29	19 7/
(9) CONSTRUCTION:	Date well drilling machine moved off of well	11-1	19 7/
Well seal-Material used Bentomite	Drilling Machine Operator's Certification:		
Well sealed from land surface to	This well was constructed under my d	irect super	vision.
Diameter of well bore to bottom of sealin.	Materials used and information reported all best knowledge and belief.	bove are true	to my
Diameter of well bore below seal		ate //-/	107/
Number of sacks of cement used in well seal sacks	(Drilling Machine Operator)		., 19
Number of sacks of bentonite used in well seal sacks	Drilling Machine Operator's License No	455	••••••
Brand name of bentonite National			
Number of pounds of bentonite per 100 gallons	Water Well Contractor's Certification:		
or water lbs./100 gals.	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.		
Was a drive shoe used? I Yes I No Plugs Size: location ft. Did any strata contain unusable water? I Yes No	Name ROBINSON EOLA Drilling		
Type of water? depth of strata	Address 4511 DAILAS Rd	N.W. S	t) A/cza
Method of sealing strata off			
Was well gravel packed? Yes No Size of gravel:	[Signed] (Water Well Contract	(or)	
Gravel placed from ft. to ft.		/-/	1071
11.	Contractor a License No Date		., 19 <i>7!</i>