NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the

STATE ENGINEER, SALEM, OREGON 97310

Was well gravel packed? 🗌 Yes 📮 No

Gravel placed from ..

WATER WELL REPORT
STATE OF OREGON AUG 2 1 1974 state Well No. 45/1W-26

(Please type or print) STATE ENGINEERstate Permit No. 6-8128

of well completion. (Do not write abo	ve this lin SALEM. OREGON		
1) OWNER:	(10) LOCATION OF WELL:		
Character Brane	County Marion Driller's well nur	mber	<del></del>
162 lith	1/4 1/4 Section 26 T. 48	R. 1w	W.M.
Address 402 402 Hubbard, Oregon	Bearing and distance from section or subdivision	n corner	
(2) TYPE OF WORK (check):	Dearing the Control of the Control o		
Abondon 🗆			
New Well Deepening Reconditioning Abandon Landrage Reconditioning Abandon Landrage Reconditioning Land	(11) WATER LEVEL: Completed we	ell.	
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found	96	ft.
Rotary Driven Domestic Tindustrial Municipal D	Static level 53 ft. below land st	urface. Date	<u>7-30-</u> 7
Cable Jetted   Dug   Bored   Irrigation   Test Well   Other	Artesian pressure lbs. per square	e inch. Date	
CASING INSTALLED: Threaded Welded 12 Welded 13 Gage 250	(12) WELL LOG: Diameter of well be Depth drilled 205 ft. Depth of complete	eted well	205 ft.
" Diam. fromft. toft. Gage  " Diam. fromft. toft. Gage  PERFORATIONS: Perforated? ▼ Yes □ No.	Formation: Describe color, texture, grain size a and show thickness and nature of each stratur with at least one entry for each change of format position of Static Water Level and indicate principle.	n and aquiter t tion. Report each	h change in
370-0 77 4 6	MATERIAL	From To	swl
Type of perforator used Mills Knife	Top soil	0 2	
Size of perforations 3/8 in. by 37 in.	Brown clay	2 21	
perforations from	Brown sandy clay	21 56	
300 perforations from 184 ft. to 201 ft.	Blue clay	56 73	
perforations fromft.	Grey sandy clay	73 79	
(7) SCREENS: Well screen installed?   Yes  No	Black silt	79 84	
Manufacturer's Name	Grey clay	84 96	
	Black sand	96 10	
TypeModel Noft. toft.	Sand and Gravel	105 11	
Diam. Slot size Set from ft. to ft.	Gravel	112 12	
	Grey elay	123 13	
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	Grey sandy clay	136 14	1
	Black silt	141 14	.7
Was a pump test made? I Yes I No If yes, by whom? Stettlers	Grey sandy clay	147 16	57
Yield: 650 gal./min. with 52 ft. drawdown after 8 hrs.	Black sand	167 17	<i>'</i> 6
H H H	Grey clay	176 18	34
" "	Black sand & gravel	184 20	
Bailer test gal./min. with ft. drawdown after hrs.	Grey clay	202 20	
Artesian flow g.p.m.			
perature of water Depth artesian flow encounteredft.	Work started 5-17 1974 Complete		19 74
(9) CONSTRUCTION:	Date well drilling machine moved off of well	7-30	1974
Well seal—Material usedCement	Drilling Machine Operator's Certification This well was constructed under my	direct sup	ervision.
Well sealed from land surface to	Materials used and information reported	. above are t	rue to my
Diameter of well bore to bottom of seal in.	best knowledge and belief	7	30 7).
Diameter of well bore below sealin.	[Signed] (Drilling Machine Operator)	Date7-2	<u>)0,</u> 1914
Number of sacks of cement used in well seal sacks	Drilling Machine Operator's License No.	7.6	51
Number of sacks of bentonite used in well seal sacks			
Brand name of bentonite	Water Well Contractor's Certification:		
Number of pounds of bentonite per 100 gallons	This well was drilled under my jurisc	liction and th	is report is
of water	true to the best of my knowledge and be	elief.	
Was a drive shoe used? Yes No Plugs Size: location 1t.	Name William D. Christenson	Jr. (Type or	nrint)
Did any strata contain unusable water? Tyes No	(Person, firm or corporation)  Address P. 20. Bey 31.3 Hubba		
Type of water? depth of strata	Audiess /// /// Sel	$Z \sim Z$	
Method of sealing strata off	[Signed] What Char	Con O	
— — Circ of grovel:	(Water Well Con	tractor)	