NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the

WATER RESOURCES DEPARTMENT. SALEM, OREGON 97310

Method of sealing strata off

Was well gravel packed? 🔀 Yes 🗌 No

20

ft. to

WATER WELL REPORT ECT VED STATE OF OREGON MAR 201978 Well No. (Please type or print)

,	V/AT	ER	RESOL	JRCE'S	DEPT.	(7
		-	_		A	1

of well completion. (Do not write abo	SALEM, OPEGON	Appl. G-8774			
1) OWNER:	(10) LOCATION OF WELL:				
` '	County Marian Driller's well nu	ımber			
Name Stauffer Bros.	14 14 Section 26 T.45	R. 1W	W.M.		
Address Hubbard, Oregon 97032	Bearing and distance from section or subdivisi	on corner			
(a) MVDE OF WORK (check):	Bearing and distance from section of subdivisi	on correct			
(2) TYPE OF WORK (check):					
New Well Abandon Reconditioning Abandon		11			
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed w	eii.			
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found	85	ft.		
Rotary 🏗 Driven 🗌 Domestic 🖂 Industrial 🗎 Municipal 🗍	Static level 41 ft. below land s	surface. Date $3/1$	4/78		
Cable	Artesian pressure lbs. per squar	re inch. Date			
CASING INSTALLED: Threaded □ Welded X	(12) WELL LOG: Diameter of well	below casing			
18 " Diam. fromO ft. to2O ft. Gage14"	Depth drilled 197 ft. Depth of completed well 197 ft. Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated,				
12 " Diam. from +2 ft. to 197 ft. Gage 4"					
" Diam. from ft. to ft. Gage					
	with at least one entry for each change of forma position of Static Water Level and indicate prin	tion. Report each cl	nange in		
PERFORATIONS: Perforated? Types In No.		T - 			
Type of perforator used Pre-perforated pipe	MATERIAL	From To	swL		
Size of perforations 1/4 in. by 2 in.	Surface	0 3			
Size of perforations /4 in. by 2 in. 960 perforations from 112 ft. to 132 ft.	Brown clay	3 44			
480 perforations from 168 ft. to 178 ft.	Blue clay	44 85			
perforations fromft. toft.	Red sand & gravel	85 91	····		
	Blue sandy clay	91 99			
(7) SCREENS: Well screen installed? Yes I No	Black sand	99 105			
Manufacturer's Name	Sand & gravel	105 134			
TypeModel No.	Blue clay	134 164			
Diam. Slot size Set from ft. to ft.	Black sand & gravel	164 179			
Diam Slot size Set from ft. to ft.	Blue clay	179 197			
(8) WELL TESTS: Drawdown is amount water level is lowered below static level -41					
Was a pump test made? Ty Yes [] No If yes, by whom? driller					
700					
Yield: 1000 gal./min. with 33 ft. drawdown arter 0 ms.					
1500 8					
7 2000 7 75					
Bailer test gal./min. with ft. drawdown after hrs.					
Artesian flow g.p.m.					
poerature of water Depth artesian flow encountered ft.	Work started Dec 16 19 77 Comple		1978		
(9) CONSTRUCTION:	Date well drilling machine moved off of well	Mar 17	1978		
Well seal—Material used Cement	Drilling Machine Operator's Certification	l :			
Well sealed from land surface to	This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief				
Diameter of well bore to bottom of seal 24 in.					
Diameter of well bore below seal	[Signed] John de Mar 17, 1978				
Number of sacks of cement used in well seal30sacks	(Drilling Mackine Operator)				
How was cement grout placed?	Drilling Machine Operator's License No.		***************************************		
Pressure grout pump	Window Win II Combined and Combined and				
***************************************	Water Well Contractor's Certification:				
	This well was drilled under my jurise true to the best of my knowledge and be	nction and this r	eport is		
Was a drive shoe used? Yes No Plugs Size: location ft.	11				
Did any strata contain unusable water P Yes No	Name John T. Miller (Person, firm or corporation)	(Type or pri	nt)		
Type of water? depth of strata	Address 1780 Tomlin Ave. Woo	dburn, Ore	97071		

Size of gravel:

197. ft.

[Signed]

Contractor's License No. 277

Mar 17

Date