NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the

WATER RESOURCES DEPARTMENT, SALEM, OREGON 97310 within 30 days from the date of well completion.

WATER WELL REPORT 7659
STATE OF OREGON
(Please type or print) State Permit No. G-10029

(Do not write above this line)

(1) OWNER:	(10) LOCATION OF WELL:	
Name Bill Schurr	County Marion Driller's well r	number 79-12-R
Address 1560 - 95th Ave. N.E.	34 34 Section 24 T. 7S	R. 2W W.M.
Salem Oregen 97303	Bearing and distance from section or subdivis	
(2) TYPE OF WORK (check):		
New Well Deepening Reconditioning Abandon		
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed v	roll
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found	45
Rotary Driven Domestic Industrial Municipal		
Dug Bored Irrigation T Test Well Other	7	surface. Date 8-1-70
CASING INSTALLED: Threaded To Welded 57	los. per squa	re inch. Date
	(12) WELL LOG: Diameter of well	below casing8
8 " Diam from + 1 ft. to 80 ft. Gage 250	Depth drilled 205 ft. Depth of comp	1-4-4 OOK
" Diam from ft. to ft. Gage		
" Diam. from ft. to ft. Gage	and show thickness and nature of each stratu	im and aguides
PERFORATIONS: Perforated? Yes No.	with at least one entry for each change of forma position of Static Water Level and indicate prin	tion Panort sock shows
Type of perforator used	MATERIAL	T _ T _ T
Size of perforations in. by in.		From To SWL
perforations from ft. to ft.	Tep seil Brewn Clay	0 2
perforations from		2 45
perforations from		
(7) CODEDIC	Blue Rock	90 110
were server matanett; 1es 140	Fractured Blue Rock	110 130
Manufacturer's Name	Blue Reck	130 200
Type Model No Diam. Slot size Set from ft. to ft.	Basalt	200 205 20
Diam. Slot size Set from ft. to ft.		
(8) WELL TESTS: Drawdown is amount water level is lowered below static level		
Was a pump test made? Yes No If yes, by whom?	1 - 40 60 73 81 6 15 63 63	
Yield: gol/min with	ALC: 2-11079	
gar, min. with it. drawdown after hrs.		
" " "	WATER RESOURCES DEPT	
	SALEM, OREGON	
American disconsistent and a second s		
8. P.M.		
perature of water 52 Depth artesian flow encountered ft.	Work started 8-2 19 79 Complete	d 8-9 1979
(9) CONSTRUCTION:	Date well drilling machine moved off of well	8-10 19 79
Well seal—Material used Cement	Drilling Machine Operator's Certification:	
Well sealed from land surface to 20	This well was constructed under my	direct supervision
Diameter of well bore to bottom of sealin.	Materials used and information reported best knowledge and belief.	above are true to my
Diameter of well bore below seal		Date 8-22 1979
Number of sacks of cement used in well sealsacks	(Drilling Machine Operator)	,
How was cement grout placed?	Drilling Machine Operator's License No	978
pressure grouted from bottom	Water Wall Contractor's Contract	
	Water Well Contractor's Certification:	
Was a drive sheet words TV. The	This well was drilled under my jurisdic true to the best of my knowledge and belie	tion and this report is
Was a drive shoe used? Yes [] No Plugs Size: location ft.	Name Flores Well Drilling	
Did any strata contain unusable water? Yes No		
Type of water? depth of strata	Address 12143 River Rd.N.E.	Gervais, 97026
Method of sealing strata off	[Signed] Thomas Felore	ai
Was well gravel packed? [Yes No Size of gravel:	(Water Well Contrac	etor)
Gravel placed from ft. to ft.	Contractor's License No. 590 Date	8-22 19 79