NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report
are to be filed with the

WATER RESOURCES DEPARTMENT, SALEM, OREGON 97310 within 30 days from the date of well completion.

WATER WELL REPORT

STATE OF OREGON

(Please type or print)

(Do not write above this line)

	-
AN ARIState	well No. 75/2W-24
7660 State	Permit No.

	,
(1) OWNER:	(10) LOCATION OF WELL:
Name BILL SCHURR	County MARION Driller's well number 79-12-R
Address 1560 - 95TH AVE.N.E.	
SALEM, OREGON 97303	Bearing and distance from section or subdivision corner
(2) TYPE OF WORK (check):	bearing and distance from section of subdivision corner
New Well ☐ Deepening ☐ Reconditioning ☐ Abandon ☐	
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Double at which waster and the same
Rotary Driven Domestic Dindustrial Municipal D	
Cable	Static level ft. below land surface. Date Artesian pressure lbs. per square inch. Date
(5) CASING INSTALLED: Threaded Welded	
"Diam. from ft. to ft. Gage	(12) WELL LOG: Diameter of well below casing
	Depth drilled ft. Depth of completed well ft.
" Diam. fromft. toft. Gage	Formation: Describe color, texture, grain size and structure of materials;
	and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in
(6) PERFORATIONS: Perforated? Yes No.	position of Static Water Level and indicate principal water-bearing strata.
Type of perforator used	MATERIAL From To SWL
Size of perforations in. by in.	AMENDED WELL LOG: CORRECT WELL SEAL ACCORDING
perforations from ft. to ft.	TO SPECIAL STANDARDS UNDER DATE OF 2-19-80
perforations from ft. to ft.	SID DRILLED WELL WITH 6" TO A DEPTH OF 18 FEET,
perforations from ft. to ft.	PRESSURE GROUTED WITH BENTONITE, 5 BAGS.
(7) SCREENS: Well screen installed? Yes No	
Manufacturer's Name	
Type Model No.	
Diam, Slot size Set from ft. to ft.	
Diam Slot size Set from ft. to ft.	
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	- KEGEIVEU
Was a pump test made? ☐ Yes ☐ No If yes, by whom?	FEB221980
gal./min. with ft. drawdown after hrs.	WATER RESOURCES DEP
ii n n	SALEM, OREGON
n " " " "	- Orthodox Orthodox
Bailer test gal./min. with ft. drawdown after hrs.	
sian flow g.p.m.	
The sture of water Depth artesian flow encountered ft.	Work started 19 Completed 19
(9) CONSTRUCTION:	Date well drilling machine moved off of well 19
Well seal—Material used	Drilling Machine Operator's Certification:
Well sealed from land surface toft.	This well was constructed under my direct supervision.
Diameter of well bore to bottom of sealin.	Materials used and information reported above are true to my best knowledge and belief.
Diameter of well bore below seal in.	[Signed] Charas orlare Date 2-20 1080
Number of sacks of cement used in well seal sacks	(Drilling Machine Operator)
How was cement grout placed?	Drilling Machine Operator's License No. 978
The state of the s	Water Well Contractor's Certification:
	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Was a drive shoe used? Yes No Plugs Size: location ft.	Name FLORES WELL DRILLING
Did any strata contain unusable water? Yes No	(Person, firm or corporation) (Type or print)
Type of water? depth of strata	Address12143 RIVER RD. N.E. GERVAIS, ORE 97026
Method of sealing strata off	[Signed] Thomas Eloub
Was well gravel packed? Yes No Size of gravel:	(Water Well Contractor)
Gravel placed from ft. to ft.	Contractor's License No590 Date2-20 , 19.80