

RECEIVED 11 30 76 68 [X] [X] MARI

NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report are to be filed with the

WATER RESOURCES DEPARTMENT, SALEM, OREGON 97310
STATE OF OREGON (Please type or print)

State Well No. 75/2w-2469
State Permit No. G-8614

WATER RESOURCES DEPT. SALEM, OREGON
DEC 26 1978
(Do not write above this line)

(1) OWNER:

Name Harold DeVries
Address 8434 Delphinium Pl. NE
Salem, Oregon 97303

(2) TYPE OF WORK (check):

New Well Deepening Reconditioning Abandon
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary Driven
Cable Jetted
Dug Bored

(4) PROPOSED USE (check):

Domestic Industrial Municipal
Irrigation Test Well Other

CASING INSTALLED: Threaded Welded
12" Diam. from plus 1 ft. to 193 ft. Gage 250
" Diam. from ft. to ft. Gage
" Diam. from ft. to ft. Gage

PERFORATIONS: Perforated? Yes No.
Type of perforator used
Size of perforations in. by in.
..... perforations from ft. to ft.
..... perforations from ft. to ft.
..... perforations from ft. to ft.

(7) SCREENS: Well screen installed? Yes No
Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS: Drawdown is amount water level is lowered below static level
Was a pump test made? Yes No If yes, by whom?
Yield: gal./min. with ft. drawdown after hrs.
" " " " " "
" " " " " "
~~Water~~ test app. 1000 gal./min. with 145 ft. drawdown after 3 hrs.
Artesian flow g.p.m.
..... erature of water Depth artesian flow encountered ft.

(9) CONSTRUCTION:
Well seal—Material used Bentonite (National Brand)
Well sealed from land surface to 22 ft.
Diameter of well bore to bottom of seal 16 in.
Diameter of well bore below seal 12" to 193' & 8" to 330'
Number of sacks of Benta used in well seal 2 sacks
How was Bentonite placed? Gravity

Was a drive shoe used? Yes No Plugs Size: location ft.
Did any strata contain unusable water? Yes No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? Yes No Size of gravel:
Gravel placed from ft. to ft.

(10) LOCATION OF WELL:

County Marion Driller's well number
NE 1/4 NW 1/4 Section 24 T. 7S R. 2W W.M.
Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.

Depth at which water was first found 194 ft.
Static level 44 ft. below land surface. Date 11/20/78
Artesian pressure lbs. per square inch. Date

(12) WELL LOG: Diameter of well below casing 8"
Depth drilled 330 ft. Depth of completed well 330 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
Top Soil	0	1	
Clay Brown	1	56	
Conglomerate Dirty Tight Brown	56	123	
Conglomerate Loose Grey	123	151	
Clay Sticky Blue & Grey	151	186	
Rock Loose Grey	186	193	
Basalt Grey & Green	193	221	WB
Basalt Hard Grey	221	270	
Basalt Medium Green & Brown	270	330	WB

Work started 11/10 19 78 Completed 11/18 19 78
Date well drilling machine moved off of well 11/20 19 78

Drilling Machine Operator's Certification:
This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.
[Signed] Thomas J. Stahl Date 11/27, 19 78
(Drilling Machine Operator)
Drilling Machine Operator's License No. 860

Water Well Contractor's Certification:
This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Name West Coast Drilling Co., Inc.
(Person, firm or corporation) (Type or print)
Address 220 Academy St., Mt. Angel, Oregon 97362
[Signed] Charles E. Stahl
(Water Well Contractor)
Contractor's License No. 519 Date 11/27, 19 78