

NOTICE TO WATER WELL CONTRACTOR: The original and first copy of this report are to be filed with the

RECEIVED AUG 28 1970

RECEIVED SEP 16 1970

MARI. 7671 4/1W-26

STATE ENGINEER, SALEM, OREGON (Please type or print) within 30 days from the date of well completion.

STATE ENGINEER SALEM, OREGON 6-6406

STATE ENGINEER SALEM, OREGON

(1) OWNER:

Name Stauffer Bros. Address Hubbard, Oregon

(2) TYPE OF WORK (check):

New Well [x] Deepening [] Reconditioning [] Abandon [] If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary [x] Driven [] Cable [] Jetted [] Dug [] Bored []

(4) PROPOSED USE (check):

Domestic [] Industrial [] Municipal [] Irrigation [x] Test Well [] Other []

CASING INSTALLED:

22" Diam. from 0 ft. to 80 ft. Gage 1/4" 12" Diam. from 0 ft. to 146 ft. Gage 1/4"

(6) PERFORATIONS:

Perforated? [x] Yes [] No. Size of perforations 3/8 in. by 5 in. 360 perforations from 104 ft. to 130 ft.

(7) SCREENS:

Well screen installed? [] Yes [x] No Manufacturer's Name Type Model No. Diam. Slot size Set from ft. to ft.

(8) WATER LEVEL: Completed well.

Static level 49 ft. below land surface Date 7/15/70 Artesian pressure lbs. per square inch Date

(9) WELL TESTS:

Drawdown is amount water level is lowered below static level. Was a pump test made? [x] Yes [] No. Yield: 1050 gal./min. with 25 ft. drawdown after 4 hrs. 1700 " " 49 " " 4 " "

(10) CONSTRUCTION:

Well seal-Material used Well Gel Bentonite Depth of seal 80 ft. Diameter of well bore to bottom of seal 25 in. Were any loose strata cemented off? [] Yes [x] No Depth Was a drive shoe used? [] Yes [x] No Did any strata contain unusable water? [] Yes [x] No Type of water? depth of strata Method of sealing strata off Was well gravel packed? [x] Yes [] No Size of gravel: 1/4" round Gravel placed from 70 ft. to 146 ft.

(11) LOCATION OF WELL:

County Marian Driller's well number 1/4 Section 26 T. 4S R. 1W W.M. Bearing and distance from section or subdivision corner

(12) WELL LOG:

Diameter of well below casing Depth drilled 146 ft. Depth of completed well 146 ft. Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level as drilling proceeds. Note drilling rates.

Table with columns: MATERIAL, From, To, SWL. Rows include Surface, Brown sandy clay, Blue sandy clay, Broken sand & gravel, Blue sandy clay, Sand, Sand & gravel, Blueclay.

Work started June 10 1970 Completed July 15 1970 Date well drilling machine moved off of well July 15 1970

Drilling Machine Operator's Certification: This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.

[Signed] John T. Miller Date July 20, 1970 (Drilling Machine Operator)

Drilling Machine Operator's License No. 26

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

NAME John Truman Miller (Person, firm or corporation) (Type or print)

Address P.O. Box 342 Hubbard, Oregon

[Signed] John T. Miller (Water Well Contractor)

Contractor's License No. 277 Date July 20, 1970