NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report
are to be filed with the

WATER RESOURCES DEPARTMENT, SALEM, OREGON 97310 within 30 days from the date of well completion.

WATER WELL REPORT

STATE OF OREGON

(Do not write above this line)

H)	MAR	1682	1
State	Well No. /S	BW-02	2

(Please type or print)

State Permit No. ..

(1) OWNER:	(10) LOCATION OF WELL:		
Name Clarence Simmons	County Marion Driller's well nu		
Address 3472 Howell Prairie Rd. NE	NW 14 NE 14 Section 25 T. 7S	r. 2W w	7.M.
Silverton, Oregon 97381	Bearing and distance from section or subdivisi	ion corner	
(2) TYPE OF WORK (check):			
New Well 🗌 Deepening 🚰 Reconditioning 🗍 Abandon 🗍			
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed w	rell.	
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found	297	ft.
Rotary X Driven Domestic Industrial Municipal	Static level 9 ft. below land	surface. Date 9/1	2/7
☐ Jetted ☐ Irrigation 🖺 Test Well ☐ Other ☐			
(5) CASING INSTALLED: ORIGINAL Threaded Welded	(12) WELL LOG: Diameter of well	below casing 8"	
	Depth drilled 405 ft. Depth of comp		ft.
			riole
" Diam. from ft. to ft. Gage	Formation: Describe color, texture, grain size and show thickness and nature of each stratu with at least one entry for each change of formation.	um and aquifer penetra	ated,
(6) PERFORATIONS: Perforated? Yes No.	position of Static Water Level and indicate pri	ncipal water-bearing st	rata.
` '	MATERIAL	From To SW	WL
Type of perforator used	·	157 183	
Size of perforations in. by in.	Basalt Hard Grey Basalt Med. Brown	183 189	
perforations from ft. to ft.		189 297	
perforations from ft. to ft.	Basalt Hard Grey Basalt Weathered Brn.	1-03 271	
perforations from ft. to ft.	Basalt Weathered Brn. & Blk.	297 307 W	ĪΒ
(7) SCREENS: Well screen installed? Yes No		307 314	ليل ا
	Basalt Hard Grey		
Manufacturer's Name	Basalt Weathered Green		VB.
Type Model No	& Brown	330 391	<u> 110</u>
Diam. Slot size Set from ft. to ft.	Basalt Hard Grey	391 405	
Diam. Slot size Set from ft. to ft.	Clay Sticky Grey	1391 403	
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	CECEIVED		
a pump test made? Yes No If yes, by whom?	0.000.000		
Yield: gal./min. with ft. drawdown after hrs.	SEP 2 1 1979	 	
" " "	WATER RESOURCES DEF	,	
" " "	SALEM, OREGON	1	
ATR	SALEM, OREGON		
			
Assesian flow g.p.m.	0/27 70	0/10	
Temperature of water Depth artesian flow encountered ft.	Work started 9/11 1979 Comple	71,	19 7
(9) CONSTRUCTION: ORIGINAL	Date well drilling machine moved off of well	9/12 1	19 7
	Drilling Machine Operator's Certification	a:	
Well seal—Material used	This well was constructed under m	y direct supervis	ion.
Well sealed from land surface to ft,	Materials used and information reported	d above are true to	my
Diameter of well bore to bottom of seal in.	best knowledge and belief.	9/13	, 7C
Diameter of well bore below seal in.	(Drilling Machine Operator)	Date9/13, 19	
Number of sacks of cement used in well seal sacks	Drilling Machine Operator's License No.	720	
How was cement grout placed?	- Special Spec		
	Water Well Contractor's Certification:		
	This well was drilled under my juris	diction and this repo	ort is
42	true to the best of my knowledge and b	elief.	
Was a drive shoe used? Yes Yes No Plugs Size: location ft.	Name WEST COAST DRILLING	O. INC.	
Did any strata contain unusable water? Yes No	(Person, firm or corporation)	Mt. Angel. O	R C
Type of water? depth of strata	Address 220 Academy St.,	ATT CT OF	<u>::></u>
Method of sealing strata off	I Malles "	MARCHI	
	[Signed] (Water Well Cor	ntractor)	
Was well gravel packed? ☐ Yes ⊠ No Size of gravel:		- /	ים סו
Guarant rate and Guarant for the fit	Contractor's License No. 519 Date		