NOTICE TO WATER WELL CONTRACTOR The original and first copy WATER WELL REPORT E IVE Date Well No. 75/20-25-66 of this report are to be filed with the (Please type or print) JAN241977 STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date R State Permit No. (Do not write above this line) of well completion. WATER RESOURCES DEPT. (10) LOCATION OF WELL: (1) OWNER: Clarence Simmons County Marion Driller's well number Name 3472 Howell Praire Rd. N.e. Silverton, Or. N.W. 34 N.W. 34 Section 25 W.M. Bearing and distance from section or subdivision corner (2) TYPE OF WORK (check): Reconditioning [Abandon 🗌 Deepening 🗷 New Well If abandonment, describe material and procedure in Item 12. (11) WATER LEVEL: Completed well. Depth at which water was first found 270 first new water , (4) PROPOSED USE (check): (3) TYPE OF WELL: ft. below land surface. Date 10/26/76 Rotary Driven | Static level Domestic | Industrial | Municipal | Jetted Cable П Irrigation 🌋 Test Well 🗌 Other lbs. per square inch. Date Artesian pressure Bored 🔲 Dug CASING INSTALLED: Threaded [] Welded 🔀 (12) WELL LOG: Diameter of well below casing 10 Diam. from Orige ft. to ft. Gage Depth drilled 420 ft. Depth of completed well" Diam. from ft. to ft. Gage Formation: Describe color, texture, grain size and structure of materials; ________ ft. to ______ ft. Gage _____ and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata. PERFORATIONS: Perforated? Tyes XNo. MATERIAL From Type of perforator used 290 M.Basalt blk.Porous W.B. 267 Size of perforations in. by 351 290 H. Basalt grey perforations from ft. to ft. 358 351 Soft Claystone grey perforations from _____ ft. to ____ ft. 358 376 H. Basalt grey perforations from ft. to 376 387 Basalt weathered brn. W.B. 387 420 (7) SCREENS: H. Basalt grey Well screen installed?
Yes X No Manufacturer's Name ___ Model No. Diam. Slot size Set from ft. to ft. to ft. Set from Diam. Slot size Drawdown is amount water level is lowered below static level (8) WELL TESTS: Was a pump test made? 🗷 Yes 🗆 No If yes, by whom? Supply gal./min. with gal./min. with ft. drawdown after Bailer test g.p.m. rtesian flow Work started 10/23/76 10/25/76 Completed 19 Depth artesian flow encountered ft. mperature of water 19 Date well drilling machine moved off of well (9) CONSTRUCTION: Drilling Machine Operator's Certification: Orig. Well seal-Material used . This well was constructed under my direct supervision. Materials used and information reported above are true to my Well sealed from land surface to best knowledge and belief. Diameter of well bore to bottom of seal in. Date 10/26/76 19 Diameter of well bore below sealin. Number of sacks of cement used in well seal Drilling Machine Operator's License No. Number of sacks of bentonite used in well seal Brand name of bentonite Water Well Contractor's Certification: Number of pounds of bentonite per 100 gallons This well was drilled under my jurisdiction and this report is lbs./100 gals. true to the best of my knowledge and belief. Name Stadeli Drilling Co.

Mt. Angel Oregon Was a drive shoe used? 🗌 Yes 🖺 No Plugs Size: location ft. (Type or print) Did any strata contain unusable water? 🗌 Yes 🛂 No Address depth of strata Type of water? Method of sealing strata off [Signed] (Water Well Contractor) Was well gravel packed? Yes No Size of gravel: Contractor's License No. 519 Date 10/26/76 19 Gravel placed from ft. to