M171.7.778)

NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report are to be filed with the STATE ENGINEER, SALEM, ORNGON 97310 2 1000 (Please type or print)

State Well No. $7/2\omega-27N$

within 30 days from the date JAN 31 1966 Please type of well completion.	e or print; State Permit No.	
1) OWNER: STATE ENGINEER	(11) WELL TESTS: Drawdown is amount water level is lowered below static level	-
Vame Lyman Behut SALEM OREGON	Was a pump test made? ▼ Yes □ No If yes, by whom? Stettle	er_
Address 6840 State St.	Yield: 140 gal./min. with 50 ft. drawdown after 1	hrs.
Salem, Ore.	n n	
(2) LOCATION OF WELL:	n u n	<u>"</u>
County Marion Driller's well number 154	Bailer test gal./min. with ft. drawdown after	hrs.
SW 14 SW 14 Section 27 T. 7S R. 2W W.M.	Artesian flow g.p.m. Date Temperature of water Was a chemical analysis made? [] Yes 3	
Bearing and distance from section or subdivision corner	Oli	110
Scaling and distance from section of subdivision solution	(12) WELL LOG: Diameter of well below casing	
	Depth drilled 125 ft. Depth of completed well 125	ft.
	Formation: Describe by color, character, size of material and structure show thickness of aquifers and the kind and nature of the material in stratum penetrated, with at least one entry for each change of form	, and
	show thickness of aguijers and the kind that hattare of the stratum penetrated, with at least one entry for each change of form	ation.
		го
(3) TYPE OF WORK (check):		3 1
Well ₩ Deepening ☐ Reconditioning ☐ Abandon ☐	TOD SOLL	41
If abandonment, describe material and procedure in Item 12.	TICEDA A CTERA COTOLITA	61
	CATOLOT A CATOLOT	81
(4) PROPOSED USE (check): (5) TYPE OF WELL:		71
Domestic Industrial Municipal Rotary Driven Cable X Jetted		61
Irrigation I Test Well Other Dug Bored	Silted gravel 76' 9	01
(6) CASING INSTALLED: Threaded □ Welded \(\mathbb{M}\)	Cement gravel (loose spots) 90' 1	121
(6) CASING INSTALLED: Threaded Welded Welded Use Welded S. " Diam. from O ft. to 115t. Gage 250	Claystone (red-gritty) 112' 1	<u>25†</u>
"Diam. from		
(7) PERFORATIONS: Perforated? ▶ Yes □ No		
Type of perforator used Mills		
Size of perforations in. by 2 in.		
500 perforations from		
perforations from ft. to ft.		
perforations from		
perforations fromft, toft.		
perforations from ft. to ft.		
(8) SCREENS: Well screen installed? ☐ Yes 🋣 No		
Manufacturer's Name		
Model No		
Diam Slot size Set from ft. to ft.	Work started 12/13/6519 Completed 1/15/66	19
Diam. Slot size Set from ft. to ft. to ft.	Date well drilling machine moved off of well 1/15/66	19
(9) CONSTRUCTION:	(13) PUMP:	
Well real Material used in goal Bentonite	Manufacturer's Name Berkeley	
Well seal—Material used in seal	Type: Submersible H.P. 5	
Depth of sealft. Was a packer used?		
Were any loose strata cemented off? Yes No Depth	Water Well Contractor's Certification:	
Was a drive shoe used? ⚠ Yes ☐ No	This well was drilled under my jurisdiction and this rep	port i
Was well gravel packed? Yes No Size of gravel:	true to the best of my knowledge and belief.	
Gravel placed from ft. to ft.	NAME Pete Tolmasoff Well Drilling	•••••
Did any strata contain unusable water? ☐ Yes 📆 No	(2 6,000,) 21111 01 012 21111	
Type of water? depth of strata	Address Turner, Ore.	•••••
Method of sealing strata off	Duilling Mechino Onever Awa Tigonso No. 320	
(10) WATER LEVELS:	Drilling Machine Operator's License No. 320	
	[Signed] the old old sale	
Static level 42 ft. below land surface Date 1/15/66	(Water Well Contractor)	
Artesian pressure lbs. per square inch Date	Contractor's License No. 410 Date 1/15/66 , 1	19
	V	

(USE ADDITIONAL SHEETS IF NECESSARY)

١. الر