NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report are to be filed with the

EGEIVER

MAY 11 WATER WELL REPORT

State Well No. 4

4/1W-27D

STATE ENGINEER, SALEM, OREGON 97310

within 30 days from the date of well completion.

WATER WELL REPORTED TO THE WATER WELL REPORTED TO THE STATE OF OREGON 97310

(Please type or print)

G-3769

State Permit No.

(1) OWNER:	(11) WELL TESTS: Drawdown is amount lowered below static le	water lev	el is
Name Shady Oak Ranch, Inc.	Was a pump test made? Yes \(\bar{\chi} \) No If yes, by who		
Address 1737 N E Broadway	Yield: 400 gal./min. with 50 ft. drawdo		8 hrs.
Portland, Oregon	n n		
(2) LOCATION OF WELL:	<i>n</i>		
County Marian Driller's well number	Bailer test gal./min. with ft. drawd	own after	hrs.
27 27 10	Artesian flow g.p.m. Date		
14 14 Section 2 T. 1W R. 4S W.M. Bearing and distance from section or subdivision corner	Temperature of water Was a chemical analysis	made? 🔲	Yes 🗶 No
bearing and distance from section of subdivision corner	(12) WELL LOG: Diameter of well below co	asing1	2
	166 -		155 ft.
			
100	Formation: Describe by color, character, size of materic show thickness of aquifers and the kind and nature of stratum penetrated, with at least one entry for each continuous c	the mater	ial in each formation.
(3) TYPE OF WORK (check):	MATERIAL	FROM	TO
	Soil	0	3
Well Deepening Reconditioning Abandon	Brown sandy clay	3	78_
Il-abandonment, describe material and procedure in Item 12.	Brown sand	78	96_
(4) PROPOSED USE (check): (5) TYPE OF WELL:	Broken gravel	96	101
Domestic Industrial Municipal Rotary Driven	Green clay and sand	101	121
Irrigation	Sticky blue clay	121	128_
(C) CACING INGMALLED	Blue sandy clay	128	134
(6) CASING INSTALLED: Threaded Welded	Sand	134	138
12" Diam. from0 ft. to140 ft. Gage14"	Sticky green clay	138	347
"Diam. from ft. to ft. Gage	Sandy grey clay	147	155
ft. Gage			
(7) PERFORATIONS: Perforated? Yes No		1	
Type of perforator used Millknife			
Size of perforations 3/8 in. by 3 in.			
124perforations from 96 ft. to 101 ft.			
ft. to ft.			
perforations from ft. to ft.			
perforations from ft. to ft.			
perforations from ft. to ft.			
(8) SCREENS: Well screen installed? ☐ Yes 🛣 No			<u> </u>
Manufacturer's Name			
Model No.			
Dram Slot size Set from ft. to ft.	Work started March 31 19 66 Completed Ann		
Diam. Slot size Set from ft. to ft.	Date well drilling machine moved off of well	11 22	19 66
(9) CONSTRUCTION:	(13) PUMP:	11 22	¹⁹ 66
Puddled Mud			
well seal—Material used in seal	Manufacturer's Name	***************************************	
Depth of seal24 ft. Was a packer used? Diameter of well bore to bottom of seal 15½ in.	Type: H.P.		
Were any loose strata cemented off? \(\partial\) Yes \(\mathbb{N}\) No Depth	Water Well Contractor's Certification:		
Was a drive shoe used? \(\text{Yes} \) \(\text{XNo} \)	This well was drilled under mer invitable		
Was well gravel packed? [Yes X No Size of gravel:	This well was drilled under my jurisdiction a true to the best of my knowledge and belief.	ind this	report is
Gravel placed from ft. to ft.	Take Massacra		
Did any strata contain unusable water? 🔲 🧏 No	(Person, firm or corporation) (Type or print)		
Type of water? depth of strata	Address P 0 Box 42 Hubbard, Oregon		
Method of sealing strata off			
(10) WATER LEVELS:	Drilling Machine Operator's License No26.		•••••
1 1 man of a	[Signed] John Journey By	le	
Static level 46 ft. below land surface Date 4/22/66	(Water Well Contractor)		·····
Artesian pressure Ibs. per square inch Date	Contractor's License No. 277 Date April	26	., 19.66