STATE OF OREGON

### RECL

# WATER WELL REPORT (as required by ORS 537.765)

JAN 1 4 1986 ASE TYPE of PRINT

M 1 71. (8349)	75/18-9cc
'IN INK	deep.

(for official use only)

(1) OWNER: SALEM, OREGON	(10) LOCATION OF WELL by legal description:			
Name Ernest Klopfenstein	County Marion SW & SW & of Section 9 of			
Address 11745 Kaufman Road NE	Township 7 South , Range 1 East W.S. , WM. (Township is North or South) , Range 1 East or West)			
City Silverton StateOR	Tax Lot Block Subdivision			
(2) TYPE OF WORK (check):	MAILING ADDRESS OF WELL (or nearest address)  Same as #1.			
New Well / ☐ Deepening 🛣 Reconditioning 🗆 Abandon 🗆	Danie as #1.			
If abandonment, describe material and procedure in Item 12.	(44) WARRING FRIED ACCORDING THE F			
(3) TYPE OF WELL: (4) PROPOSED USE (check):	(11) WATER LEVEL of COMPLETED WELL:			
Rotary Air 🔀 Driven 🗌 Domestic 🗆 Industrial 🗀 Municipal 🗆 Thermal:	Depth at which water was first found 225 ft.			
Rotary Mud Dug Irrigation X Withdrawal Reinjection	Static level 60 ft. below land surface. Date 12/31/85			
Cable Bored D Other:  Piezometric Grounding Test	Artesian pressure lbs. per square inch. Date  (12) WELL LOC. Dispersor of well below spaning 5 7/8"			
CASING INSTALLED: Steel  Plastic  Depth drilled  85  ft. Depth of completed  Exemption Describe color texture grain size and structure of materials				
Threaded Welded Formation: Describe color, texture, grain size and structure of materi				
ft. Gauge	formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.			
LINER INSTALLED: Steel    Plastic    Welded	MATERIAL From To SWL			
	Basalt **X*X* grey hard seamy 223 230			
ft. toft. Gauge	and crevicy.			
(6) PERFORATIONS: Perforated?   Yes  No	Basalt grey hard 230 276 WB			
Size of perforations in. by in.	Basalt grey hard seamy porous 276 278			
perforations from ft. to ft.	Crevice space 278 279 WB			
perforations from	Basalt grey hard seamy 279 308			
perforations from				
(7) SCREENS: Well screen installed? ☐ Yes ₺ No				
Manufacturer's Name				
Type				
Diam. Slot Size Set from L. ft. to ft.				
Diam Slot Size				
(8) WELL TESTS: Drawdown is amount water level is lowered below static level				
Was a pump test made? ☐ Yes ☒ No If yes, by whom?				
Yield: gal./min. with ft. drawdown after hrs.				
Air test 150 gal./min. with drill stem at 307 ft. 1 hrs.				
Bailer test gal./min. with ft. drawdown after hrs.				
Artesian flow g.p.m.				
Temperature of water Depth artesian flow encounteredft.	Determine to test of 12/26/85 (completed 12/31/85)			
CONSTRUCTION: Special standards: Yes \( \sigma \) No \( \sigma \)	Date work started			
Well seal—Material used Cement ORIGINAL	Date well drilling machine moved off of well 12/31/85 19			
Well sealed from land surface to	(unbonded) Water Well Constructor Certification (if applicable):			
Diameter of well bore to bottom of seal in.	This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.			
Diameter of well bore below seal in.	[Signed] Don Stalely Date 12-31, 19 85			
Amount of sealing material sacks pounds	[Signed] Date Date Date Date Date Date Date Date			
How was cement grout placed?	(bonded) Water Well Constructor Certification:			
	Bond 5122718 Issued by: Safeco Insurance of America			
Was pump installed? NO Type HP Depth ft.	(Surety Company Name) On behalf of R. Stadeli & Sons. Inc. (type or print name of Water Well Constructor)			
Was a drive shoe used?				
Did any strata contain unusable water?   Yes  No	This well was drilled under my jurisdiction and this report is true to the			
Type of Water? depth of strata	best of my knowledge and belief:			
Method of sealing strata off	(Signed) Taul (Water Well Constructor)			
Was well gravel packed? ☐ Yes ☒ No Size of gravel:	(Signed) Jaul S. Water Well Constructor)  (Dated) 12-31-85 (Water Well Constructor)			
Gravel placed from	(DAVO)			
	CD144666 GD2			

#### STATE OF OREGON

## RECL

### Maria e en com

M171. 8349

75/1E-9 CC Jesp. (for official use only)

WATER WELL REPORT (as required by ORS 537.765)

JAN 1 4 1986 ASE TYPE OF PRINT IN INK

(1) OWNER:	SALEM, CREGON	(10) LOCATION OF WELL by lega			:
Name Ernest Klop		County Marion SW 4 SW 4 6	of Section _	9	of
Address 11745 Kaufn		Township 7 South Range 1 Ed	AS L (Range is Eas	t or West)	, WM.
City Silverton	State OR .	Tax Lot Lot Block Subdivision			
(2) TYPE OF WORK	(check):	MAILING ADDRESS OF WELL (or nearest address)			
New Well	_	Same as #1.			
If abandonment, describe material					
		(11) WATER LEVEL of COMPLET	ED W	ELL:	
(3) TYPE OF WELL:		Depth at which water was first found 225			ft.
Rotary Air 🛛 Driven 🗌	Thermal:	*	land surfac	e. Date 1	2/31/85
Rotary Mud 🔲 Dug 🔲	Irrigation		square incl		.2101100
Cable 🗆 Bored 🗀	Piezometric Grounding Test	- International Property	5	7/8	1
CASING INSTAI	LLED: Steel \( \text{\text{M}} \) Plastic \( \text{\text{Threaded}} \) Welded \( \text{\text{\text{M}}} \)	(12) WELL LOG: Diameter of well below casing   7/8			
" Diam. fromORIG	NAL ft. Gauge 250	and nature of each stratum and aquifer penetrated, with at formation. Report each change in position of Static Wa	least one en	try for ea	ch change of
" Diam. from		water-bearing strata.			<del></del>
LINER INSTALI	$ \begin{array}{c cccc} \mathbf{LED:} & \mathbf{Steel} & \square & \mathbf{Plastic} & \square \\ & \mathbf{Threaded} & \square & \mathbf{Welded} & \square \\ \end{array} $	MATERIAL	From	То	SWL
" Diam. from		Basalt \XXXX grey hard seamy	223	<u>230.</u>	
		and crevicy.			
(6) PERFORATIONS		Basalt grey hard	230	276	WB
Size of perforations	in. by	Basalt grey hard seamy porous	276	278	
	perforations from ft. to ft.	Crevice space	278	279	WB
	perforations from ft. to ft.	Basalt grey hard seamy	279	308	
	perforations from ft. to ft.				
<b>.</b>	ell screen installed? ☐ Yes 🏖 No				
	Model No				
	Size Set from ft. to ft.				
	Size				
(8) WELL TESTS:	Drawdown is amount water level is lowered below static level				
Was a pump test made?   Yes	☑ No If yes, by whom?				
Vield:	gal./min. with ft. drawdown after hrs.				<u> </u>
	u u u				
Air test 150	gal./min. with drill stem at 307 ft. 1 hrs.				<u> </u>
Bailer test	gal./min. with ft. drawdown after hrs.				<u> </u>
Artesian flow	g.p.m.				
Temperature of water	Depth artesian flow encountered ft.	12/26/05	1 12	/31/8	E
CONSTRUCTION	N: Special standards: Yes □ No □	Date work started 12/26/85 /comple		/ 31/0	
	Cement ORIGINAL		31/85		19
7720000	ft.	(unbonded) Water Well Constructor Certific			
Diameter of well bore to bottom o		This well was constructed under my direct su	pervision.	Materia	ıls used and
Diameter of well bore below seal		information reported above are true to my best kn			_
	sacks D pounds D	[Signed] Signed]	Date	C2/	
	Sucre II pound	d 1 N W to W II Constructor Contificat	·		
		(bonded) Water Well Constructor Certificat Bond 5122718 Issued by: Safeco II (number) (Si	ISULTANCE urety Compar	of Ar	nerica_
Was pump installed?No	Type HP Depth ft.	R. Stadeli & Sons.	Inc.	-	
_		(type or print name of V	√ater Well Co	nstructor)	ř.
Was a drive shoe used?		This well was drilled under my jurisdiction	and this r	eport is	true to the
Type of Water?	depth of strata	best of my knowledge and belief.	,	A.	
		(Signed) Gaul S. Sto	Ser		
Method of sealing strata off  Was well gravel packed?   Ye	s 🗵 No Size of gravel:	(Signed) Jaul S. (Water Well Constru (Dated) 12-31-85	ctor)		
Was well gravel packed?	D KAT TAO DIZE OF Braver	(Dated) /d - 3/-85			