NOTICE TO WATER WELL CON ACTOR The original and first conformation of this report are to be filed with the STATE ENGINEER, SALEM, OREGON OF THE OF OREGON Within 30 days from the date of well completion.

(Do not write above this line)

RT SYS	State Wel	75/	IE-	26
MARI.	State Per	<b> </b>	-	
(e)				

(1) OWNER:	(10) LOCATION OF WELL:	,
Delbert Hupp	County Marion Driller's well nu	mber
Address Star Rt Silverton, Treg	/4 /4	R. W.M.
	Bearing and distance from section or subdivision 2200 E. & 300 N. of S.W. Cor se	m corner
(2) TYPE OF WORK (check):	2200 E.& 300 N. of S.W. Cor se	CZO • T • \ \( \text{CD • II • \ \text{FP • TP • } \)
New Well ☐ Deepening █ Reconditioning ☐ Abandon ☐		
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed we	ell.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 26 8	ft.
The state of the s	Static level 203 ft. below land s	urface. Date 10/27/72
Cable		
Dug ☐ Bored ☐ Irrigation <b>K</b> Test Well ☐ Öther ☐	Artesian pressure lbs. per squar	
CASING INSTALLED: Threaded   Welded F	(12) WELL LOG: Diameter of well be Depth drilled 505 ft. Depth of completion: Describe color, texture, grain size a	eted well 505 ft.
PERFORATIONS: Perforated? * Yes   No.	and show thickness and nature of each stratur with at least one entry for each change of format position of Static Water Level and indicate prin	n and aquifer penetrated, tion. Report each change in
a denth	MATERIAL	From To SWL
•	Orig Depth	221
Size of perforations in. by in.  24 perforations from 185 ft. to 205 ft.	Winthord basalt Brn.	221 237
	H. Basalt grey	237 268
perforations from ft. to ft.	Weathered basalt brm. W.B.	268 273
perforations from ft. to ft.	H. basalt grey	273 295
(7) SCREENS: Well screen installed?   Yes  No	Weathered basalt brn. W.B	295 358
Manufacturer's Name	H. basalt grey & brn. seams	358 402 W.B.
Type Model No	H. basalt grey	402 505
Diam. Slot size Set from ft. to ft.	Some water coming around	1
Diam. Slot size Set from ft. to ft.	Some was - Commission	
(8) WELL TESTS: Drawdown is amount water level is lowered below static level		
Was a pump test made? * Yes   No If yes, by whom? Driller		
yield: 33 gal./min. with 290 ft. drawdown after 3 hrs.		
" " " " "		
" " "		
Bailer test gal./min. with ft. drawdown after hrs.		
Artesian flow g.p.m.	Work started 10/19/72 19 Complete	ted 10/27/72 19
perature of water Depth artesian flow encounteredft.	Work started 10/19/72 19 Complete Date well drilling machine moved off of well	10/27//72
(9) CONSTRUCTION:	1	
Well seal-Material used trig 5	Drilling Machine Operator's Certification This well was constructed under my	; , direct cunervision
Well sealed from land surface toft.	Materials used and information reported	above are true to my
Diameter of well bore to bottom of seal in.	best knowledge and belief.	
There are not seen to be a below good in	[Signed David Machine Operator	Date 11/6/72, 19
Number of sacks of cement used in well seal sacks	Drilling Machine Operator's License No.	322
Number of sacks of cement used in well seal sacks  Number of sacks of bentonite used in well seal sacks	Dritting Machine Operator's License No.	
Brand name of bentonite	Water Well Contractor's Certification:	
Number of pounds of bentonite per 100 gallons	This well was drilled under my jurisc	liction and this report is
of waterlbs./100 gals.	true to the best of my knowledge and be	lief.
Was a drive shoe used? Yes 🗆 No Plugs Size: locationft.	Name R. St adell & Sons Inc.	
Did any strata contain unusable water?   Yes No	(Person, firm pr corporation)  Address Silverton, Oreg	(Type or print)
Type of water? depth of strata	Address 111Ve12011.015	1 1.
Method of sealing strata off	[Signed] Taul X. Stat	Illa.
Was well gravel packed? 🗌 Yes 💆 No Size of gravel:	(Water Well Cont	
Gravel placed from ft. to ft.	Contractor's License No. 296 Date 1	<u>1/6/72</u> , <sub>19</sub>