NOTICE TO WATER WELL CONTRACTOR
The original and first copy
of this report are to be
filed with the

STATE ENGINEER, SALEM, ORESON 97310 within 30 days from the date of well completion.

WATER WELL REPORT EIVED

STATE OF OREGON JUL 1 1975

State Well No.

	<i>f</i>
	85/14/-13
١.	07,00

(Please type WATER RESOURCES DEPT. Permit No.
(Do not write above this STALEM, OREGON

(1) OWNER:	(10) LOCATION OF WELL:	·	
Name Mr. & Mrs. Lyman L. Sundvall	County Marion Driller's well no	mber 790	
Address Rte.2, Box 523, Aumsville		R. 1W W.M.	
	Bearing and distance from section or subdivisi-		
(2) TYPE OF WORK (check):	O Dasary and	OII COINCE	
New Well 🙀 Deepening 🗌 Reconditioning 🗀 Abandon 🗀			
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed w		
(3) TYPE OF WELL: (4) PROPOSED USE (check):	-		
Rotary & Driven	Depth at which water was first found	65 _ ft.	
Cable		urface. Date $6/19/75$	
Dug Bored I Irrigation Test Well Other	Artesian pressure O lbs. per squar	e inch. Date	
(5) CASING INSTALLED: Threaded Welded W	(12) WELL LOC.	ell	
6 "Diam. from 0 ft. to 19 ft. Gage . 250	(12) WELL LOG: Diameter of well below casing 6"		
	Depth drilled 142 ft. Depth of compl		
" Diam. fromft. toft. Gage	Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in		
DEDECT A TIONS			
PERFORATIONS: Perforated? Yes No.	position of Static Water Level and indicate prin	cipal water-bearing strata.	
Type of perforator used	MATERIAL	From To SWL	
Size of perforations in. by in.	Ton soil	0 * 5 *	
perforations from ft. to ft.	Claystone (red-brown)	5* 8*	
perforations from ft. to ft.	Basalt (weathered)	8 14	
perforations from ft. to ft.	Basalt (black-hard)	14 t 50 t	
(7) SCREENS: Well screen installed? [7] Ves. M. No.	Basalt & shale (marbled)	50° 65°	
Well screen installed? ☐ Yes No Manufacturer's Name	Basalt (grey-brown)	65' 70'	
Type Model No.	Basalt (grey-green)	70 t 72 t	
Diam. Slot size Set from ft. to ft.	Basalt (grey black)	72' 90'	
Diam. Slot size Set from ft. to ft.	Basalt (brown-red)	90 * 93 * 93 * 93 * 93 * 93 * 93 * 93 *	
	Basalt (grey-green) Basalt (black-hard)	93° 100° 100°142° 0°	
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	Dasaro (brack-nard)	100 142 0	
Was a pump test made? Yes No If yes, by whom?			
Yield: gal./min. with ft. drawdown after hrs.			
" " "			
Air lift 60 gpm after 2hr from 140 ft/			
Dellar And			
Artesian flow 3 g.p.m.			
perature of water Depth artesian flow encountered ft.	perature of water Depth artesian flow encountered		
(9) CONSTRUCTION:	Date well drilling machine moved off of well	6/19/75 19	
Well seal—Material used Cement	Drilling Machine Operator's Certification:		
Well sealed from land surface to	This well was constructed under my	direct supervision.	
Diameter of well bore to bottom of seal	Materials used and information reported above are true to my best knowledge and belief.		
Diameter of well bore below seal6 in.	[Signed] 10 Johnay Pate 6/23 , 1975		
Number of sacks of cement used in well seal	(Drilling Machine Operator)		
Number of sacks of bentonite used in well seal sacks	Drilling Machine Operator's License No.	3.20	
Brand name of bentonite	Worker Wall Control to C. 110.		
Number of pounds of bentonite per 100 gallons	Water Well Contractor's Certification:		
of water lbs./100 gals.	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.		
Was a drive shoe used? \square Yes Σ No Plugs Size: location ft.	Name Pete Tolmasoff Well Drilling		
Did any strata contain unusable water? 🗌 Yes 😰 No	(Person, firm or corporation)	(Type or print)	
Type of water? depth of strata	Address Turner, Ore.		
Method of sealing strata off	(x, t, 1 n)	mal of	
Was well gravel packed? ☐ Yes K No Size of gravel:	[Signed] (Water Well Contra	ector)	
Gravel placed from	Contractor's License No. 10 Date 6/	, ,	
16. 10 1t.	Contractor's License No Date .Q/	<i>EU/</i> , 19	