

File Original and First Copy with the STATE ENGINEER, SALEM, OREGON

RECEIVED JUN 20 1960 STATE ENGINEER SALEM, OREGON

WATER WELL REPORT

M 1 1. 8994

State Well No. 8/1W-30J

STATE OF OREGON G 1946

State Permit No.

(1) OWNER:

Name Francis Hendriks Address Rt. 1 Box 47 Aumsville, Ore.

(2) LOCATION OF WELL:

County Marion Owner's number, if any-- Bearing and distance from section or subdivision corner

(3) TYPE OF WORK (check):

New Well [X] Deepening [] Reconditioning [] Abandon []

(4) PROPOSED USE (check):

Domestic [X] Industrial [] Municipal [] Irrigation [X] Test Well [] Other []

(5) TYPE OF WELL:

Rotary [] Driven [] Cable [X] Jetted [] Dug [] Bored []

(6) CASING INSTALLED:

8 5/8" Diam. from 2/3-0 ft. to 117 ft. Gage 250

(7) PERFORATIONS:

Perforated? [] Yes [X] No Type of perforator used SIZE of perforations in. by in.

(8) SCREENS:

Well screen installed [] Yes [X] No Manufacturer's Name Model No. Slot size Set from ft. to ft.

(9) CONSTRUCTION:

Was well gravel packed? [] Yes [] No Size of gravel: Gravel placed from ft. to ft. Was a surface seal provided? [] Yes [] No To what depth? ft. Material used in seal-- Did any strata contain unusable water? [] Yes [] No Type of water? Depth of strata Method of sealing strata off

(10) WATER LEVELS:

Static level 67 ft. below land surface Date 5/18/60 Artesian pressure lbs. per square inch Date

Log Accepted by:

[Signed] Francis Hendriks Date May 18, 1960 (Owner)

(11) WELL TESTS:

Drawdown is amount water level is lowered below static level Was a pump test made? [X] Yes [] No If yes, by whom? Stottler Yield: 135 gal./min. with 42 ft. drawdown after 1 hrs. 220 " 82 " 1 " 250 " 153 " 2 "

(12) WELL LOG:

Diameter of well 8 inches. Depth drilled 270 ft. Depth of completed well 270 ft.

Formation: Describe by color, character, size of material and structure, and show thickness of aquifers and the kind and nature of the material in each stratum penetrated, with at least one entry for each change of formation.

Table with columns MATERIAL, FROM, TO. Rows include Top soil, Yellow clay, Terrace gravels, Weathered volcanic ash, Volcanic ash carboniferous, Andesite basalt (fresh), Volcanic ash (greenish), Old land surface, Andistie basalt (vesicular), Hole was reamed to 10" dia. down to 116 ft. to take 8 5/8 casing. Back filled annular space first with 3/4 - gravel 16 ft then 1/2 - crushed rock 2 cu ft then completed filling to top of hole with drillings.

Work started 5/2 19 60 Completed 5/18 19 60

(13) PUMP:

Manufacturer's Name Type: H.P.

Well Driller's Statement:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

NAME Robinson Drilling & Supply (Person, firm, or corporation) (Type of print)

Address 140 Pine St. NE Salem, Ore.

Driller's well number 8/1W-30J1

[Signed] Harry A. Robinson (Well Driller)

License No. 22 Date 5/20/60, 19.

