ORIGINAL File Original, and Duplicate with the	LERS REPORT Do Not State Well No. 4/W-33 R(1)
	REGON RY 7.4 Fill In State Permit No. 6500
(1) OWNER: Name Schmidt's Hatchery MAR 2 ! 1977	(10) WELL PESTS:
Address Rte 1 STATE ENGINEE	Was a pump test made? M Yes No If yes, by whom? driller Yield: 110 gal/min. with 2 d ft draw down after the
Hubbard, Oregon SALFM OREGON	
	<u>" 140 " 50 " 4 "</u>
(2) LOCATION OF WELL:	Artesian flow
County Marian Owner's number, if any— R. F. D. or Street No. Rte 1	Shut-in pressurelbs. per square inch.
Bearing and distance from section or subdivision corner	Bailer test g.p.m. with ft. drawdown
	Temperature of water Was a chemical analysis made? ☐ Yes ☐ No Was electric log made of well? ☐ Yes ☑No
67	
C. C	(11) WELL LOG:
(3) TYPE OF WORK (check):	Diameter of well, inches.
New well K Deepening ☐ Reconditioning ☐ Abandon ☐	Total depth 129 ft. Depth of completed well 129 ft.
f abandonment, describe material and procedure in Item 11.	Formation: Describe by color, character, size of material and structure, and show thickness of aquifers and the kind and nature of the material in each stratum penetrated, with at least one entry for each change of formation.
(4) PROPOSED USE (check): (5) EQUIPMENT:	stratum penetratea, with at least one entry for each change of formation. ft. to ft.
momestic A Industrial Municipal Rotary	0" 2" Soil
' Irrigation M Test Well □ Other □ Cable M Dug Well □	2" 18" Clav
(a) Cacarra michael	18" 97" Sandy clay
Threaded Welded X	97" 99" Gray clay 99" 104" Black Sand
Gage or Diameter from to	10/." 110." 510.
FROM ft. to ft. Diam. 8 Wall of Bore ft. ft.	104" 112" Black sand and gravel 112" 114" Gravel
" " "Standard " " " " " " " " " " " " " " " " " " "	114" 118" Sand
" " " " "	118" 123 "6" Gravel
11 11 11 11 11	123 * 6" 126 * 9" Sand 126 * 9" 129 " Gravel
Through the state of the second state of the	126 9" 129" Gravel
Type and size of shoe or well ring Size of gravel: Describe joint	11 13
	n n
(7) PERFORATIONS:	D 17
Type of perforations 13 in., length, by 3/8 in.	11 11
FROM ft. to ft. perf per foot No. of rows	n n
" 112 " 114 " 8 " " " 2 " " "	n n
" 118 " 123 \$6" 8 " " 8 " " "	"
	11 11
SCREENS:	n n
Give Manufacturer's Name, Model No. and Size	11 11
de de la companya de	21 11
(8) CONSTRUCTION:	"
Was a surface sanitary seal provided? ☐ Yes No To what depth ft.	33
Were any strata sealed against pollution? Yes No If yes, note depth of strata	Ground elevation at well site feet above mean sea level.
FROM ft. to ft.	Work started Dec 9 19 55 Completed Dec 22 1855
19 29 39 31 31 32 32 32 32 32 32 32 32 32 32 32 32 32	Well Driller's Statement: This well was drilled under my jurisdiction and this report is true to the best of my knowledge with the left of the best of my knowledge.
METHOD OF SEALING	true to the best of my knowledge and belief.
(9) WATER LEVELS:	NAME John Truman Miller
Depth at which water was first found ft.	(Person, firm, or corporation) (Typed or printed)
Standing level before perforating 14 6" ft.	Address Rte 1 Box 259 Hubbard, Oregn
Standing level after perforating 14.611 ft.	Driller's well number
Log Accepted by:	[Signed] I fred miller
[Signed] Weller Samuel Dated Les 29, 1955	License No. 39 Dated December 23,55
and the state of t	Particular Dates Comment Comme