The original and first copy of this report are to be filed with the

filed with the STATE OF OREGON
STATE ENGINEER, SALEM, OREGON TO THE ENGINEER, SALEM, OREGON Within 30 days from the date of well completion.

SALEM OR (Do not Write above this line)

State Permit No.

(1) OWNER:	(10) LOCATION OF WELL:
Name Bill Peters	County Marion Driller's well number
AddresRt 1 Box 354, Hubbard, Oregon	14 Section 33-34 T.4S R. LW W.M.
	Bearing and distance from section or subdivision corner
(2) TYPE OF WORK (check):	
New Well 🔀 Deepening 🗌 Reconditioning 🗎 Abandon 🔲	The second secon
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 30 ft.
Rotary Driven Domestic Domestic Municipal Domestic Rotary	Static level 25 ft. below land surface. Date 6/2/72
Cable of Setted	
Dug Bored I Irrigation Test Well Other	Artesian pressure lbs. per square inch. Date
(5) CASING INSTALLED: Threaded Welded T	(12) WELL LOG: Diameter of well below casing 6
6 "Diam. from 0 ft. to 111 ft. Gage -250	Depth drilled 113 ft. Depth of completed well 111 ft.
ft. Gage	
	Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated,
A PERSONA TYONG	with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.
PERFORATIONS: Perforated?   Yes   No.	position of Static water Level and indicate principal water-vearing straid.
Type of perforator used	MATERIAL From To SWL
Size of perforations in. by in.	Soil. Brown 0 3
perforations fromft. toft.	Sand. Brown 3 18
perforations from ft. to ft.	Sand, Brown WB 18 20 5
perforations from ft. to ft.	
(F) CODEENIC.	
	Sand, Brown WB 30 60 20
Manufacturer's Name	Clay, Gray 60 63
Type Model No.	Sand, Black WB 63 92 35
Diam. Slot size Set from ft. to ft. Diam. Slot size Set from ft. to ft.	Clay, Gray 92 100
Diani. State	Sand, Black WB 100 105   45
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	Sand, Black, Gravel, Small
Was a pump test made? ☐ Yes ☒ No If yes, by whom?	WB 105 111 25
	v :2
	A series areas a decimal a recipio della di di Maria. Application della di di Maria della di
	THE STATE OF THE SECOND STATE OF THE SECOND
" " " "	which was been also the second of the second
Bailer test 25 gal./min. with 25 ft. drawdown after 1 hrs.	
Artesian flow g.p.m.	
perature of water Depth artesian flow encounteredft.	Work started $6/1/72$ 19 Completed $6/2/72$ 19
(9) CONSTRUCTION:	Date well drilling machine moved off of well $6/3/72$ 19
Rentonite & Cement	Drilling Machine Operator's Certification:
well seal—Material used	This well was constructed under my direct supervision.
Well sealed from land surface toft.  Diameter of well bore to bottom of sealin.	Materials used and information reported above are true to my best knowledge and belief.
Diameter of well bore below seal in. 2	
Number of sacks of cement used in well seal sacks	[Signed] H. Blackman Date 7/14/72 19
Number of sacks of hentonite used in well seal	Drilling Machine Operator's License No681
Brand name of bentonite Central Oregon	
Number of pounds of bentonite per 100 gallons	Water Well Contractor's Certification:
of water Ibs./100 gals.	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Was a drive shoe used? TYes   No Plus Size: location ft.	place the second of the secon
Did any strata contain unusable water? Yes 🗆 No	Name Harvey Blackman (Person, firm or corporation) (Type or print)
Type of water?Surface depth of strata 18	Address Rt 1 Box 181K, Mulino, Oregon
Method of sealing strata off Casing & Bentonite	Lui Rhank
Was well gravel packed? ☐ Yes M No Size of gravel:	[Signed] Hamen (Water Well Contractor)
Gravel placed fromft. toft.	Contractor's License No. 3.7. Date 7/14/72 19
	Towns and the state of the stat