of this report are to RECE filed with the RECE STATE ENGINEER, SALEM, OREGON 97310

WATER WELL REPORT

STATE OF OREGON

(Please type or print)
(Do not write above this line)

State Well No.

within 30 days from the date OCT 1 5 1975 of well completion.

State Permit No.

WATER RESOURCES DEPT.	6-121		
1) OWNER: SALEM, OREGON	(10) LOCATION OF WELL:	ም ያለዩታ ሙ አለዩታ	1 401 045
Tame City of Salem	County Marion Driller's well num	nber XXXXXX	T.\0T0.\2D
Address 555 Liberty S. E.	NE 34 SW 34 Section 6 T. SS 1	r. 2 V	W.M.
Salem, Oregon 97301	Bearing and distance from section or subdivision	n corner	
2) TYPE OF WORK (check):			
New Well ☑ Deepening □ Reconditioning □ Abandon □			
f abandonment, describe material and procedure in Item 12.	(11) WATED I EVEL: Completed we	.11	
	(11) WATER LEVEL: Completed we	·224	£L
3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found		10-3-75
Rotary	Static level 11 ft. below land su	rface. Date	<u> </u>
Oug	Artesian pressure lbs. per square	inch. Date	
EASING INSTALLED: Threaded Welded	(19) THE LOC.	. 8	11
EASING INSTALLED: Threaded Welded Gage	(12) WELL LUG: Diameter of well below casing		
"Diam. from	Depth drilled ft. Depth of completed well it.		
" Diam. from ft. to ft. Gage	Formation: Describe color, texture, grain size a	nd structure of r	naterials; netrated
" Diam. from It. to It. Gage	and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in		
PERFORATIONS: Perforated? Yes No.	position of Static Water Level and indicate princ	ipal water-bearin	ng strata.
Type of perforator used	MATERIAL	From To	SWL
•	gravel & silt	0 2	
Mac or periorations	gravel & sand boulders	2 18	11'
perforations from	glowing sand & gravel	18 26	
perforations from	gravel & heavy sand	26 32	
perforations from ft. to ft.	black gravel & clay	32 35	
(7) SCREENS: Well screen installed? ☐ Yes ☒ No	gray gravel & sand & clay	35 41	
Manufacturer's Name	brown sand & gravel & clay	41 49	
Type Model No.	gravel & sand	49 54	
Diam Slot size Set from ft. to ft.	brown conglomerant -dry	54 57	
Diam. Slot size Set from ft. to ft.	gravel/sand	57 63	
	gravel & sand with clay	63 78	
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	clay & sand - a little gravel	78 80	
Was a pump test made? ☐ Yes 🏿 No If yes, by whom?	sand, clay & gravel-decompose	1 80 101	
Yield: gal./min. with ft. drawdown after hrs.	brown sand & gravel & clay	101 108	
" " "	gravel & sand	108 110	1
			
700 20			
Bailer test 100 gal./min. with 30 ft. drawdown after 2 hrs.			
Artesian flow g.p.m.	A 750 50F	10.2	nr.
rature of water 53 Depth artesian flow encountered ft.	Work started 9-17 19 75 Complete	ed 10-3	19 75
(9) CONSTRUCTION:	Date well drilling machine moved off of well	10-3	19 75
cement.	Drilling Machine Operator's Certification:		
Well seal—Material used 110	This wall was constructed under my	direct supe	rvision.
Well sealed from land surface toft.	Materials used and information reported best knowledge and belief.	above are tru	e w my
Diameter of well bore to bottom of seal in.	V he had straight	Date / 10 / 19	7 19 75
Diameter of well bore below sealin. 33	[Signed] (Drilling Machine Operator)		
Number of sacks of cement used in well sealsacks	Drilling Machine Operator's License No		
Number of sacks of bentonite used in well seal sacks			
Brand name of bentonite	Water Well Contractor's Certification:		
of water	This well was drilled under my jurisd true to the best of my knowledge and be	iction and this	report is
Was a drive shoe used? ∑ Yes ☐ No Plugs Size: location ft.			1
Did any strata contain unusable water? Yes No	Name Schoen Electric. & Pump. (Person, firm or corporation)	(Type or p.	rint)
	Address 626 W. Queen Averue	- Albany,	Or. 9732
Type of water? depth of strata	Jan. 19	la -	
Method of sealing strata off	[Signed] (Water Well Cont	rector) :	
Was well gravel packed? ☐ Yes ¾ No Size of gravel:		~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~	2
Gravel placed from ft. to	Contractor's License No513. Date /	f//	