WATER WELL REPORT STATE OF OREGON



State Well No.

State Permit No.

WATER RESOURCES DEPT. SALEM, OREGON

1) OWNER:	(10) LOCATION OF WELL:
Name Heritage Seedlings, INC	County Marion Driller's well number 2726
Address 4199 75th St. S.E.	4 4 Section 10 T. 8S R. 2W W.M.
City Salem, Oregon 97301 State	Tax Lot # Lot Blk Subdivision
2) TYPE OF WORK (check):	Address at well location: 4194 71st St. S.E.
New Well □ Deepening □ Reconditioning \ Abandon □	
f abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.
	Depth at which water was first found existing ft.
3) TYPE OF WELL: (4) PROPOSED USE (check): Pump Hoist	Static level 51 ft. below land surface. Date 9/3/87
Air Driven Domestic Lindustrial Diminicipal D	Artesian pressure lbs. per square inch. Date
Mud	(12) WELL LOG: Diameter of well below casing6
(5) CASING INSTALLED: Steel Plastic	Depth drilled ft. Depth of completed well 153 ft.
5) CASING INSTALLED: Steel Plastic Threaded Welded	Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry
	for each change of formation. Report each change in position of Static Water Level
" Diam. from ft. to ft. Gauge	and indicate principal water-bearing strata.
LINER INSTALLED:	MATERIAL From To SWL
4" Diam. from ft. to 153 ft. Gauge 160PSI	When existing pump in well broke and was re-
	moved from well, the pumpman found that rocks
(6) PERFORATIONS: Perforated? XI Yes \(\subseteq \text{No Liner} \) Type of perforator used \(Skilsaw \) Only	had fell on top of pump. The pumpman was con-
Size of perforations 1/8 in. by 8 in.	cerned thex about putting a new pump in the
180 perforations from 93 ft. to 1.53 ft.	well without a liner first being installed.
perforations from	Threefore we used the pumphoist already over
perforations from ft. to ft.	the well to install a liner before the new
	pump was installed. The liner bettomed out
(7) SCREENS: Well screen installed? Yes X No Manufacturer's Name	at 153 feet.
Type	This well was originally firilled for Mark
Diam. Slot Size Set from ft. to ft.	Krautmann by Sneed Drilling Co. on 8/22/84
Diam. Slot Size Set from ft. to ft.	
Drawdown is amount water level is lowered	
Capacity and Flow remained unchanged a pump test made? Yes X No If yes, by whom?	
Yield: gal./min. with ft. drawdown after hrs.	
Air test gal./min. with drill stem at ft. hrs.	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
Design test gal/min. with ft. drawdown after hrs.	
Temperature of water Depth artesian flow encountered ft,	Work started 9/3/87 19 Completed 9/3/87 19
	Work started 9/3/87 19 Completed 9/3/87 19 Date well drilling machine moved off of well 9/3/87 19
(9) CONSTRUCTION: Special standards: Yes \(\text{No } \) No \(\text{No } \)	
Well seal—Material used Seal Not Disturbed	Drilling Machine Operator's Certification:
Well sealed from land surface to	This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.
Diameter of well bore to bottom of searin. Diameter of well bore below sealin.	[Signed] Date 9/4/, 19.87.
Number of sacks of cement used in well seal sacks	(Drilling Machine Operator) Drilling Machine Operator's License No
How was cement grout placed?	
200 Hall College Brown page 1	Water Well Contractor's Certification:
	This well was drilled under my jurisdiction and this report is true to
Was pump installed? Type HP Depth ft.	the best of my knowledge and belief. Name WILLAMETTE DRILLING CO
Was a drive shoe used? $\ \square$ Yes $\ \square$ No $\ $ Plugs Size: location ft.	(Person, first or corporation) Address 7365 0 Neil Rd. N.E. Salem, Oregon 9730
Did any strata contain unusable water? Yes No	Address 7365 0 Nepl Rd. N.E. Salem, Oregen 9/30
Type of Water? depth of strata	[Signed] Mak D Dea
Method of sealing strata off	(Water Well Contractor)
Was well gravel packed? ☐ Yes ☐ No Size of gravel:	Contractor's License No. 7.5.3
Gravel placed from ft. to ft.	