NOTICE TO WATER WELL CONTRACTOR

water resources department. C WATER WELL REPO

WATER RESOURCES DEPARTMENT. C WATER OF OREGON

SALEM, OREGON 97310

within 30 days from the date
of well completion.

WATER

WATER WELL REPO

(Please type or print) WATER WELL REPORT

JUN 2 5 1986 not write above this line)

State Permit No.

WATER PESOURCES DEPT	and the same of th	
(1) OWNER: SALEM, OREGON	(10) LOCATION OF WELL:	
Name Jerry Olson	County Marion Driller's well number	
Address 26350 SW 45 Th DR.	14 14 Section /O T. 85 R. 2W	<u>w.m.</u>
Willsonkille, Oregon 97070	Bearing and distance from section or subdivision corner	
(2) TYPE OF WORK (check):		
New Well 🗲 Deepening 🗌 Reconditioning 🔲 Abandon 🗌		
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.	
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 205	ft.
Domestic ► Industrial ☐ Municipal ☐	Static level 35 ft. below land surface. Date 4-12	-80
Dug	Artesian pressure lbs. per square inch. Date	
(5) CASING INSTALLED: Threaded Welded	(12) WELL LOG: Diameter of well below casing	
6 "Diam. from #/ ft. to 120 ft. Gage . 250	Depth drilled 228 ft. Depth of completed well 228	ft.
ft. Gage ft. Gage	Formation: Describe color, texture, grain size and structure of mate	
" Diam. from ft. to ft. Gage	and show thickness and nature of each stratum and aquifer penet	rated,
(A) DEDUCE A STORY C.	with at least one entry for each change of formation. Report each changosition of Static Water Level and indicate principal water-bearing s	nge in strata.
(6) PERFORATIONS: Perforated? Yes No.		wL
Type of perforator used		
Size of perforations in. by in.	Top Soil 0 1	
perforations fromft. toft.	DRIOMPOSED ROCK 33 113	
perforations fromft. toft.	Biack Basalt 113 135	
perforations from ft. to ft.	Weathered Basalt 135 141	
(7) SCREENS: Well screen installed? Yes No	Red Bed Rock Airm 141 155	
Manufacturer's Name	Tan Vay Stone Firm 155 160	
Type Model No.	Badly weathered Basalt 160 172	
Diam. Slot size Set from ft. to ft.	Tan Vay Stone 172 178	
Diam. Slot size Set from ft. to ft. to ft.	Black Puttifued wood 205 207	
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	Black Pettifyed Wood 205 207 aray Clay Stone 207 210	
s a pump test made? Yes No If yes, by whom?		351
Yield: gal./min. with ft. drawdown after nrs.	205'- 210' 8 G.P.M.	
	210' - 220' 67 B.P.M.	
"Air Test May Fluctuate"		
test 75 gal./min. with 193 ft. drawdown after hrs.		
Artesian flow g.p.m. Temperature of water Depth artesian flow encounteredft.	Work started 4-8 1980 Completed 4-12	19 8 0
(9) CONSTRUCTION:	Date well drilling machine moved off of well 4-12	19
Well seal—Material used	Drilling Machine Operator's Certification:	
Well sealed from land surface to	This well was constructed under my direct supervi Materials used and information reported above are true t	sion.
Diameter of well bore to bottom of sealin.	best knowledge and belief.	0 1113
Diameter of well bore below seal	[Signed] J.D. Mondon Date 4-15,	19.80
Number of sacks of cement used in well sealsacks	(Drilling Machine Operator) Drilling Machine Operator's License No	
How was cement grout placed?	Drining Machine Operator's Literise 140:	
Hastibuston Method	Water Well Contractor's Certification:	
	This well was drilled under my jurisdiction and this rep true to the best of my knowledge and belief.	ort is
Was a drive shoe used? Yes [] No Plugs Size: location ft.	Name Miller, West Well Drilling	
Did any strata contain unusable water? Yes No	(Person, firm or corporation) (Type or print)	
Type of water? depth of strata	Address 5875 gaffin Rd. St. Salen	и
Method of sealing strata off	[Signed] Max Mordell	
Was well gravel packed? [] Yes No Size of gravel:	(Water Well Contractor)	
Gravel placed from ft. to ft.	Contractor's License No. 746 Date 4-15,	1920