NOTICE TO WATER WELL CONTRACTOR The original and first copy of this copy of this are to be filed with the	L REPORT	- /2/11-10
WATER RESOURCES DEPARTMENT OCT 91978 STATE OF SALEM, OREGON 97310 OCT 91978 (Please type	OREGON State Well No.	,/40/0

of well completion. WATER RESOURCES. DEPTite at	love this line	
(1) OWNER:	(10) LOCATION OF WELL:	M
Name Joseph Johnson	County Marion Driffer's well number	
Address 6953 Ranay DR. 36	¼ ¼ Section / O T. 8 ≤ R. 2 W W.M.	
Salem Otroon	Bearing and distance from section or subdivision corner	
(2) TYPE OF WORK (check):	Bearing and distance from Section of Subdivision Co	rner
New Well ∰ Deepening ☐ Reconditioning ☐ Abandon ☐		
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.	
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found	47 ft.
Rotary Driven Domestic Industrial Municipal Cable Jetted Domestic	Static level 22 ft. below land surface	e. Date 9-12-7
Dug	Artesian pressure lbs. per square incl	a. Date
CASING INSTALLED: Threaded Welded Welded Welded Gage 250	(12) WELL LOG: Diameter of well below	G
ft. to ft. Gage	Depth drilled / 40 ft. Depth of completed	·
	Formation: Describe color, texture, grain size and si and show thickness and nature of each stratum an with at least one entry for each change of formation. I	d aquifer penetrated. Report each change in
PERFORATIONS: Perforated? Syes I No.	position of Static Water Level and indicate principal	water-bearing strata.
Type of perforator used / OF CA	MATERIAL Fro	m To SWL
Size of perforations 78 in. by 6 in. 15 perforations from 57 ft. to 70 ft.	Top Soil C	
	Brown Clay with	/
perforations fromft. toftftft.	Decomposed Rock 6	27
	Intak Cobbies 2	7 35
(7) SCREENS: Well screen installed? Yes E No	The Clay 3:	
Manufacturer's Name	white Clay Sticky 38	3 42
Type Model No Diam. Slot size Set from ft. to ft.	Brown Clay with	2 11 000
Diam. Slot size Set from ft. to ft.	Decomposed Rock 45	
	Black Basalt 65	
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	Weathered Basalt . 72	
Was a pump test made? [] Yes S No If yes, by whom?	Bray Basait 7k	
Yield: gal./min. with ft. drawdown after hrs.	weathured Basait 8:	
" " "	Gray Basait 87	
"A11- " " "-	Blue Breen Sindy Clay 12	3 140 22
Bailer test 25 gal./min. with//8 ft. drawdown after//2 hrs.		
Artesian flow g.p.m.		
perature of water Depth artesian flow encountered ft.	Work started 9-9 1978 Completed	9-12 1978
(9) CONSTRUCTION:	Date well drilling machine moved off of well	9-12 1978
Well seal—Material used 431911 +	Drilling Machine Operator's Certification:	
Well sealed from land surface toft.	This well was constructed under my dire Materials used and information reported above	ect supervision. e are true to my
Diameter of well bore to bottom of sealin.	best knowledge and belief.	•
Diameter of well bore below sealin. Number of sacks of cement used in well sealsacks	[Signed]	
Number of sacks of cement used in well sealsacks How was cement grout placed?sacks	Drilling Machine Operator's License No	
Air Brout Pump		
-	Water Well Contractor's Certification: This well was drilled under my jurisdiction	and this report is
Was a drive shoe used? ☑ Yes ☐ No Plugs Size: location ft.	true to the best of my knowledge and belief.	
Did any strata contain unusable water? Yes No Plugs	Name MILLER AWES I DRILLING (Person, firm or corporation) (Type or print)	
Type of water? depth of strata	Address 5875 GAFTIN Rd. S	i.E.
Method of sealing strata off	(111 inline DUMANA)	MA
Was well gravel packed? ►Yes □ No Size of gravel: ————————————————————————————————————	[Signed] (Water Well Contractor)	1 / ~
Gravel placed from 49 ft. to 70 ft.	Contractor's License No. 633 Date Sept	Ti 13 1978
	EETS IF NECESSARY)	SP*45656-119