REGEIVED

WATER WELL REPORT

JUL 1 8 1985

WATER RESOURCES DEPT WITH SALEM, OREGON STATE OF OREGON

State Well No. State Permit No.

(1) OWNER:	(10) LOCATION OF WELL:		_
Name MR. OBIE EATHERLY	County MA-210 U Driller's well number		
Address 439 CHICKADEE CT, VE.	NE 14 SW 14 Section // T. 85	number R. るい	W.M.
City SALEM State ORE.	_	/ Subdivisio	
(9) TYPE OF WORK (sheels):		RP ST.	Si W.
(2) TYPE OF WORK (check):	soum, u		
New Well Deepening □ Reconditioning □ Abandon □	(11) WATER LEVEL: Completed well.		
If abandonment, describe material and procedure in Item 12.	Depth at which water was first found 53		
(3) TYPE OF WELL: (4) PROPOSED USE (check):		and surface. Date	Tt.
Rotary Air K Driven 🗆 Domestic 🗶 Industrial 🗆 Municipal 🗆		r square inch. Dat	
P-tary Mud			4
	(12) WELL LOG: Diameter of well below of the Depth drilled 7/ ft. Depth of c		01 "
(5) CASING INSTALLED: Steel Velded Plastic Casing Threaded Welded	Formation: Describe color, texture, grain size and stru	completed well	7/ ft.
	thickness and nature of each stratum and aquifer penet	trated, with at lea	st one entry
"Diam from ft. to ft. Gauge	for each change of formation. Report each change in p and indicate principal water-bearing strata.	osition of Static	Water Level
LINER INSTALLED: YES			T
4" Diam. from 0 ft. to 9/ ft. Gauge 160	MATERIAL 700 SOL	From To	SWL
		0 4	
(6) PERFORATIONS: Perforated? ✓ Yes □ No	BASALT WEATHERE D WASHING	4 23 35	
Type of perforator used #ORO1+OV STEEL - SKILL SAW ON FIRE Size of perforations	BASALT U FIRM (W.S)	35 54	ALTESIA
	BASALT DENSE	54 26	196163191
576EL 9 perforations from 75 ft. to 53 ft.	BASALT WEATH. WASING	76 85	
P: V. C. /2 perforations from 7/ ft. to 96 ft.	BAKALT BENSE	85 89	 -
perforations from ft. to ft.	GRAN CARY (STICKED & WASHY)	89 91	
(7) SCREENS: Well screen installed? ☐ Yes ➤ No	THE CATE CATE TO THE THE	0///	+
Manufacturer's Name			
Type Model No.			*
Diam. Slot Size Set from ft. to ft.			· -
Diam. Slot Size Set from ft. to ft.			
(8) WELL TESTS: Drawdown is amount water level is lowered			
below static level	*. GRAVEL WAS ALSO PLACES		
a pump test made? Yes No If yes, by whom?	ARCHAIS P. V. C. FROM 20'		
d: gal/min. with ft. drawdown after hrs.	40 91,		
" " "			
Air test 2,7 gal./min. with drill stem at 90 ft. 2 hrs.			
Bailer test gal./min. with ft. drawdown after hrs.			
sesian flow 25 g.p.m. FROM 60° with AIR 1851			
mperature of water 57 Depth artesian flow encountered . 5.3 ft.	Work started 4-29 19 85 Complete	d 5-1	/> 1985
(9) CONSTRUCTION: Special standards: Yes \(\subseteq \) No \(\subseteq \)	Date well drilling machine moved off of well	5-1	<u>′フ 19 冬ゞ</u>
Well seal—Material used PORTLAND Coment	Drilling Machine Operator's Certification:		
Well sealed from land surface to	This well was constructed under my direct su	ipervision. Mat	erials used
Diameter of well bore to bottom of sealin.	and information reported above are true to my be	est knowledge a	and belief.
Diameter of well bore below seal	[Signed] (Drilling Machine Operator)	Date	, 19.×.>
Number of sacks of cement used in well seal Sacks	Drilling Machine Operator's License No	174	
How was cement grout placed? PRUSUAE GRUYTES WITH CEMENT PHOPS	Water Well Contractor's Certification:		
Was pump installed?	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.		
./-	Name SWEED WELL DRILL	i WG	******
Was a drive shoe used? ☐ Yes XNo Plugs	(Person, firm or corporation)	(Type o	or print)
Type of Water? depth of strata	Address 227 2007 07.	, soci	VV7
Method of sealing strata off	[Signed] Jan R. Frierd	***************************************	•••••
Was well gravel packed? XYes □ No Size of gravel: PEA	(Water Well Contractor	` 7-9	ク だい
Gravel placed from 44 ft. to 54 ft. 4527	Contractor's License No		د, 19
The state of the s			