NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the state, one of the state of the water well report of this report are to be filed with the state of th

State Well No. 4/1w - 346

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of the late of well completion.		e or print) State Permit No.		
(1) OWNER:		(11) WELL TESTS: Drawdown is amount water level is lowered below static level		
		Was a pump test made? ► Yes □ No If yes, by wh		er
Name R I. Kinsey Kuenzi		Yield: 475 gal./min. with 26 ft. draw	down after 🗜	hrs.
Address Rte 3 Bex 153 Silverton, Oregon		" 76 0 " 46 "	1	,,,
(2) LOCATION OF WELL:		25 27 29	· · · · · · · · · · · · · · · · · · ·	**************************************
• •		Dance tost	wdown after	hrs.
County Marian Driller's well		Artesian flow g.p.m. Date		
14 14 Section 35 T.	and analysis of the last of the second of th	Temperature of water Was a chemical analy		
Bearing and distance from section or subdivisi	ion corner	(12) WELL LOG: Diameter of well below	w casing12	2
- 	2 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 -	Depth drilled 136 ft. Depth of complete	i well	136 ft.
The second secon	19 14年16日本 高级的企业 11 11 11 11 11 11 11 11 11 11 11 11 11			ture, and
The second secon	· · · · · · · · · · · · · · · · · · ·	Formation: Describe by color, character, size of mat show thickness of aquifiers and the kind and nature stratum penetrated, with at least one entry for each	ch change of fo	rmation.
· · · · · · · · · · · · · · · · · · ·	and the second of the second o	MATERIAL	FROM	то
(3) TYPE OF WORK (check):		Surface	0	3
,	ditioning	Brewn sandy clay	3	31
n-pandonment, describe material and proce	dure in Item 12.	Blue sandy clay	31	69
	(5) TYPE OF WELL:	Black sand	69	99
(4) PROPOSED USE (check):	Rotary Driven D	Brown sand and gravel	99	130
Domestic Industrial Municipal	Cable Jetted	Black sand and gravel	130	136
Irrigation Test Well Other	Dug 🗌 Bored 🖺			
(6) CASING INSTALLED: Three	eaded Welded			
12." Diam. from 0 ft. to	130 ft. Gage			
" Diam, fromft, to	ft. Gage			,
" Diam. fromft_to				
			-	
,	orated? X Yes 🗍 No			
Type of perforator used Millknife Size of perforations 3/8 in. by	2 in.			
Size of perforations 3/8 in. by 128 perforations from				
perforations from perforations from		- 1125		
perforations from	ft. toft.			
perforations from				
	ft. toft.			
	talled? 🗌 Yes 🍱 No			,
<u>*</u>				
Manufacturer's Name	Model No.			
Diam. Slot size Set from ft. to ft.		Work started April 21 1965. Completed	Mov 7	1965
Diam. Slot size Set from ft. to ft.		Work started April 21 1965. Completed May 7 1965 Date well drilling machine moved off of well 19		
	Service Annual Control of the Contro			
(9) CONSTRUCTION:		(13) PUMP:		
Well seal—Material used in seal		Manufacturer's Name		,
Depth of seal 24 ft. Was a packer used? 120		Type: H.P		
Diameter of well bore to bottom of seal		Water Well Contractor's Certification:		
Were any loose strata cemented off? Yes	₽ No Depth		da a d. 17.4	
Was a drive shoe used? Yes X No	Cinn of smovel.	This well was drilled under my jurisdict true to the best of my knowledge and belief.		report is
Was well gravel packed? ☐ Yes X No	Size or graver;	John Truman Miller		•
Gravel placed fromft_ toII.		NAME (Person, firm or corporation) (Type or print)		
Did any strata contain unusuable water? I Yes No		Address P O Box 42 Hubbard, Oregon		
Type of water? depth d strata				
Method of sealing strata off		Drilling Machine Operator's License No.	277 26	**********
(10) WATER LEVELS:		[Signed] from I the		
DELVICE TO THE PROPERTY OF THE	and surface Date $\frac{5}{6}$	(Water Well Contra		
Artesian pressure Ibs. per s	quare inch Date	Contractor's License No. 26 Date M	ay7	1965

(USE ADDITIONAL SHEETS IF NECESSARY)