MORR 1127
WATER WELL REPORT EB 2 8 1975
State Well No. 5N 26E-24 NOTICE TO WATER WELL CONTRACTOR

The original and first copy
of this report are to be
filed with the

STATE ENGINEER, SALEM, OREGON within 30 days from the date of well completion.

STATE OF OREGON STATE ENGINEER

(Do not write above this lin SALEM, OREGO!) State Permit No.

(1) OWNER:	(10) LOCATION OF WELL:		
Name Rober-Thike	County Wolraw Driller's well number		
Address Rt2 Boy 203C	14 14 Section 24 T. 5 N.	R. 26E.	W.M.
Discor, Ourger 97844	Bearing and distance from section or subdivisio	n corner	
(2) TYPE OF WORK (check):			
New Well   Deepening □ Reconditioning □ Abandon □			
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed we	.11	
	_	<b>711.</b>	
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 2.2		<u> </u>
Rotary M. Driven Domestic Industrial Municipal Domestic	Static level 2.4 ft. below land su	irface. Date 2/2	1/75
D. Bored Irrigation Test Well Other	Artesian pressure lbs. per square	inch. Date	
# Diam. from	(12) WELL LOG: Diameter of well be Depth drilled \$\mathcal{A}\$ of t. Depth of completion: Describe color, texture, grain size a and show thickness and nature of each stratum	eted well 40 nd structure of mate	ft. erials;
	with at least one entry for each change of format	ion. Report each cha	nge in
perforations: Perforated?  Yes No.	position of Static Water Level and indicate princ	ipal water-bearing	strata.
Type of perforator used	MATERIAL	From To S	SWL
Size of perforations in. by in.	Topsoil	0 5	
perforations from	Sand	5 ZO	
perforations from ft. to ft.	Trave	20 40	W.B.
perforations from ft. to ft.			
(7) SCREENS: Well screen installed?   Yes X No			
Manufacturer's Name			
Type Model No			
Diam Slot size Set from ft. to ft.		<del></del>	
Diam. Slot size Set from ft. to ft.			
(8) WELL TESTS: Drawdown is amount water level is lowered below static level			
s a pump test made?  Yes 182 No If yes, by whom?			
gal./min. with ft. drawdown after hrs.			
" "			
" " "			<del></del>
iter test 200 gal./min. with 15 ft. drawdown after 1 hrs.			<del></del>
. →esian flow g.p.m.	2 - 11 - 2 - 2 - 11		10.75-
perature of water Depth artesian flow encountered ft.	Work started 2 - Z y 1975 Complete	ed 2 - 2 - 4	19 / 3
(9) CONSTRUCTION:	Date well drilling machine moved off of well  Drilling Machine Operator's Certification:	2-24	19 7.3
Well seal-Material used Sintonite	This well was constructed under my	direct supervi	ision.
Well sealed from land surface to	Materials used and information reported above are true to my		
Diameter of well bore to bottom of sealin.	best knowledge and belief. [Signed] 2 and factor Date 2/24, 1975		
Diameter of well bore below seal in.	(Drilling Machine Operator)		
Number of sacks of cement used in well seal sacks	Drilling Machine Operator's License No. 65		
Number of sacks of bentonite used in well seal	-		<del></del>
Brand name of bentonite Matiental	Water Well Contractor's Certification:		
Number of pounds of bentonite per 100 gallons	This well was drilled under my jurisd	iction and this rep	ort is
of waterlbs./100 gals.	true to the best of my knowledge and bel		
Was a drive shoe used? ⊠ Yes □ No Plugs Size: location ft.	Name TF64 GRIFFIN (Person, firm or corporation)	(Type or print)	)
Did any strata contain unusable water?   Yes  No	Address 900 HERMISTON AVE H		
Type of water? depth of strata	1 1 1 1	<i>K</i> :-	
Method of sealing strata off	[Signed] (Water Well Confu	(	
Was well gravel packed?   Yes No Size of gravel:			
Gravel placed from ft. to ft.	Contractor's License No	2-24	19Հ⊃
	HEETS IF NECESSARY)	SP*4	45656-119