NOTICE TO WATER WELL CONTRACTOR The original and first copy of this port are to be filed with the WATER WELL WATER DESCRIPCES DEPARTMENT	L REPORT	-1/		(
water resources department water of well completion. Fig. 1860 (Do not write ab	OREGON or print) ove this line) State Well No. State Permit N	/		
SALS.				
(1) OWNER:	(10) LOCATION OF WELL:			
Name Morrow County School R-1	County Maryow Driller's well number			
Address Irrigan, Oregon	SE 14 NE 14 Section 25 T. 5 N R. 26 W.M.			
	Bearing and distance from section or subdivis	ion corne	r	
(2) TYPE OF WORK (check):				
New Well ☐ Deepening ☐ Reconditioning ☐ Abandon ☐				
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.			
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 33 ft.			
Rotary Driven Domestic Industrial Municipal Industrial Domestic Information In	Static level 33 ft. below land surface. Date 7-31-			7-31-80
	Artesian pressure lbs. per square inch. Date			
(5) CASING INSTALLED: Threaded Welded War Diam, from # 1 ft. to 60 ft. Gage 250	(12) WELL LOG: Diameter of well below casing			
"Diam. fromft. toft. Gage	Depth drilled of ft. Depth of completed well ft.			
"Diam. from ft. to ft. Gage	Formation: Describe color, texture, grain size and show thickness and nature of each stratu with at least one entry for each change of forms position of Static Water Level and indicate pri	ım and a ation. Rep	quifer p ort each	enetrated, change in
(6) PERFORATIONS: Perforated? ☐ Yes ☐ No.		1		T
Type of perforator used	Sand	From	8	SWL
Size of perforations in. by in.	Large Gravel & Sand	8	26	
perforations from	Coarse Gravel & Sand	26	60	WB
perforations from ft. to ft.				
(7) SCREENS: Well screen installed? Yes No				
Manufacturer's Name	Annual Control of the	 		
Type Model No.				
Diam Slot size Set from ft. to ft.				
Diam. Slot size Set from ft. to ft.		-		
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	RECEIVED			
a pump test made? Yes No If yes, by whom?	AUGO 4 1980			-
Yield: gal./min. with ft. drawdown after hrs.	WATER RESOURCES DEPT	1		
200 gpii 78	BALEM, OREGON			
		<u> </u>		<u> </u>
iler test gal./min. with ft. drawdown after hrs.				
Temperature of water Depth artesian flow encounteredft.	Work started 7-28 1980 Complete	ted 7	'-31-	19 80
Charles and the second of the	Date well drilling machine moved off of well	7-31		19 80
(9) CONSTRUCTION: Well seal—Material used	Drilling Machine Operator's Certification	:		
Well sealed from land surface to	This well was constructed under my	direct	supe	rvision.
Diameter of well bore to bottom of seal 14 in.	Materials used and information reported best knowledge and belief	apove	are tru	le to my
Diameter of well bore below sealin.	[Signed] Nonal Mellerre	Date 2	-31	1980
Number of sacks of cement used in well seal12sacks	[Signed] Jone Date 7-31, 1980 (Drilling Machine Operator) Drilling Machine Operator's License No			
How was cement grout placed?	Drining Machine Operator's License No.		2	*********
Method C	Water Well Contractor's Certification:			
	This well was drilled under my jurisdiction and this report is			
Was a drive shoe used? ⚠ Yes ☐ No Plugs Size: location ft.	true to the best of my knowledge and belief.			
Did any strata contain unusable water?	Name Column A BASA Well (Type or print)			
Type of water? depth of strata	Address X 1961	Here	n.1.52	CN O)
Method of sealing strata off	[Signed] Suo For	1		
Was well gravel packed? ☐ Yes ☐ No Size of gravel:	(Water Well Contractor)			
Gravel placed from ft. to ft.	Contractor's License No		131	
ATTOM A DOMINION A TOM	SERVE IF NECESSARV)	7		SP*45656-119