

NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report
are to be filed with the

WATER RESOURCES DEPARTMENT
SALEM, OREGON 97310
within 30 days from the date
of well completion.

STATE OF OREGON WATER WELL REPORT

JUL 26 1977
(Please type or print)

State Well No. Sn/26E-260C
State Permit No. MORR1233

THIS WELL CAVED IN
REDRILLED IN
1979 to 103
-JB

WATER RESOURCES DEPT.
SALEM, OREGON

(1) OWNER:

Name Robert V. Gillett
Address Rt 2 Box 184
Swinger, Oregon 97844

(2) TYPE OF WORK (check):

New Well Deepening Reconditioning Abandon
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary Driven
Cable Jetted
Dug Bored

(4) PROPOSED USE (check):

Domestic Industrial Municipal
Irrigation Test Well Other

CASING INSTALLED:

Threaded Welded
10" Diam. from 0 ft. to 108 ft. Gage 250
" Diam. from " ft. to " ft. Gage
" Diam. from " ft. to " ft. Gage

PERFORATIONS:

Perforated? Yes No.
Type of perforator used
Size of perforations in. by in.
perforations from " ft. to " ft.
perforations from " ft. to " ft.
perforations from " ft. to " ft.

(7) SCREENS:

Well screen installed? Yes No
Manufacturer's Name
Type Model No.
Diam. Slot size Set from " ft. to " ft.
Diam. Slot size Set from " ft. to " ft.

(8) WELL TESTS:

Drawdown is amount water level is lowered below static level
Was a pump test made? Yes No If yes, by whom?
Yield: gal./min. with ft. drawdown after hrs.
" " " " "
" " " " "
air 700 gal./min. with 43 ft. drawdown after 1 hrs.
Artesian flow g.p.m.
Temperature of water Depth artesian flow encountered " ft.

(9) CONSTRUCTION:

Well seal—Material used Cement
Well sealed from land surface to 20 ft.
Diameter of well bore to bottom of seal 13 in.
Diameter of well bore below seal 10 in.
Number of sacks of cement used in well seal 10 sacks
How was cement grout placed?
Was a drive shoe used? Yes No Plugs Size: location " ft.
Did any strata contain unusable water? Yes No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? Yes No Size of gravel:
Gravel placed from " ft. to " ft.

(10) LOCATION OF WELL:

County Morrow Driller's well number
SW 1/4 NW 1/4 Section 26 T. 57N. R. 26E. W.M.
Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.

Depth at which water was first found 75 ft.
Static level 57 ft. below land surface. Date 7-19-77
Artesian pressure lbs. per square inch. Date

(12) WELL LOG:

Diameter of well below casing
Depth drilled 108 ft. Depth of completed well 108 ft.
Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
<u>Topsoil</u>	<u>0</u>	<u>3</u>	
<u>Gravel</u>	<u>3</u>	<u>12</u>	
<u>Sand & gravel</u>	<u>12</u>	<u>75</u>	
<u>Gravel</u>	<u>75</u>	<u>108</u>	<u>W.B.</u>

Work started 7-18 19 77 Completed 7-19 19 77
Date well drilling machine moved off of well 7-19 19 77

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.
[Signed] James T. Lutch Date 7-22, 19 77
(Drilling Machine Operator)
Drilling Machine Operator's License No. 665

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Name TROY GRIFFIN (Type or print)
Address 900 HERMISTON AVE, HERMISTON ORE (Type or print)
[Signed] Troy Griffin (Water Well Contractor)
Contractor's License No. 65 Date 7-22, 19 77