

NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report are to be filed with the

RECEIVED STATE OF OREGON STATE ENGINEER SALEM, OREGON MAR 18 1971

STATE ENGINEER, SALEM, OREGON 97310

within 30 days from the date of well completion

(Please type or print)

(Do not write above this line)

State Well No. 5N/26-26

State Permit No. MORR 1237

(1) OWNER:

Name E.L. Bettercourt Address Irrigon, Oregon

(2) TYPE OF WORK (check):

New Well [x] Deepening [ ] Reconditioning [ ] Abandon [ ]

If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary [x] Cable [ ] Dug [ ] Driven [ ] Jetted [ ] Bored [ ]

(4) PROPOSED USE (check):

Domestic [x] Industrial [ ] Irrigation [ ] Test Well [ ] Other [ ]

(5) CASING INSTALLED:

8" Diam. from 78 ft. to ... ft. Gage 250

(6) PERFORATIONS:

Perforated? [ ] Yes [x] No. Size of perforations in. by in.

(7) SCREENS:

Well screen installed? [ ] Yes [x] No Manufacturer's Name Type Model No.

(8) WELL TESTS:

Drawdown is amount water level is lowered below static level Was a pump test made? [ ] Yes [x] No Yield: 300 gal./min. with 18 ft. drawdown after 1 hrs.

(9) CONSTRUCTION:

Well seal—Material used Bentonite Well sealed from land surface to 20 ft. Diameter of well bore to bottom of seal 11 in. Diameter of well bore below seal 8 in. Number of sacks of cement used in well seal 1 sacks Number of sacks of bentonite used in well seal 1 sacks Brand name of bentonite National Number of pounds of bentonite per 100 gallons of water Was a drive shoe used? [x] Yes [ ] No Plugs Size: location ft. Did any strata contain unusable water? [ ] Yes [x] No Type of water? depth of strata Method of sealing strata off Was well gravel packed? [ ] Yes [x] No Size of gravel: Gravel placed from ft. to ft.

(10) LOCATION OF WELL:

County Morrow Driller's well number 1/4 1/4 Section 26 T. 5N R. 26 E. W.M. Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.

Depth at which water was first found 63 ft. Static level 55 ft. below land surface. Date 3-4-71 Artesian pressure lbs. per square inch. Date

(12) WELL LOG:

Diameter of well below casing Depth drilled 78 ft. Depth of completed well 78 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

Table with columns: MATERIAL, From, To, SWL. Rows: Sand (0-3), Gravel, med. (3-76), Gravel, coarse (76-78) U.S.

Work started 3-2 19 71 Completed 3-4 19 71 Date well drilling machine moved off of well 3-4 19 71

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief. [Signed] Troy Griffin Date 3/5, 1971

Drilling Machine Operator's License No. 15

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. Name TROY GRIFFIN (Person, firm or corporation) (Type or print) Address 925 HERMISTON AVE. HERMISTON ORE. [Signed] Troy Griffin (Water Well Contractor) Contractor's License No. 65 Date 3/5, 1971