NOTICE TO WATER WELL CONTRACTOR
The original and first copy
of this report are to be
filed with the

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

WATER WELL REPORT

State Well No.

STATE OF OREGON DE 7 1972 State Well No. S
(Please type Spring TE ENGINEER Permit No. 1972) (Do not write above the Ain FM OREGON

(1) OWNER:	(10) LOCATION OF WELL:	
Name Wallace A. Frederickson	County MOTTOW Driller's well nu	
Address P.O. Box 331	1/4 N.W. Section 27 T. 5 N.	R. 26 Eastwin.
Irrigon, Oregon 97844	Bearing and distance from section or subdivision corner	
(2) TYPE OF WORK (check):	450ft. south of Northweasts section corner	
New Well ☐ Deepening ☐ Reconditioning ☐ Abandon ☐	of section 27 & 70 ft. east of	
If abandonment, describe material and procedure in Item 12.	The state of the s	· · · · · · · · · · · · · · · · · · ·
	(11) WATER LEVEL: Completed we	
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 18 ft.	
Rotary	Static level 18 ft. below land su	rface. Date 4/1/72
Dug ☐ Bored ☐ Irrigation 😿 Test Well ☐ Other ☐	Artesian pressure lbs. per square	inch. Date
CASING INSTALLED: 8x8cribiam from 0 ft to 15 ft GageRailroad 12 "Diam from 15 ft to 128 ft Gage .025" "Diam from ft to ft Gage PERFORATIONS: Perforated? Yes \(\) No.	(12) WELL LOG: Diameter of well below casing	
	MATERIAL	From To SWL
Type of perforator used Mills Knife	19 114	
Size of perforations $\frac{1}{2}$ in. by 2 in.	Sand	0 15 0
18	Clay	15 18 18
perforations from ft. to ft.	Sand	18 128 18
perforations from ft. to ft.		
(7) SCREENS: Well screen installed? ☐ Yes K No		
Manufacturer's Name	· gang dan wegan to	
Type Model No ft. to ft.		
Diam. Slot size Set from ft. to ft.		
(8) WELL TESTS: Drawdown is amount water level is lowered below static level		-
Was a pump test made? Pres I No If yes, by whom? Self		
Yield: 1200 gal./min. with 15 ft. drawdown after 168 hrs.		
<i>" "</i>	· · · · · · · · · · · · · · · · · · ·	
" " "		
Bailer test gal./min. with ft. drawdown after hrs.		
Track to the state of the state		
Artesian flow g.p.m.		
Depth artesian flow encountered ft.	Work started 8/1 19 71 Complete	
(9) CONSTRUCTION:	Date well drilling machine moved off of well	8/10 19 72
Well seal—Material used Cement	Drilling Machine Operator's Certification:	
Well sealed from land surface to	This well was constructed under my	direct supervision.
Diameter of well bore to bottom of seal	Materials used and information reported above are true to my best knowledge and belief.	
Diameter of well bore below seal	[Signed] /// Francisco Date 10025 19	
Number of sacks of cement used in well seal 18 sacks	(Drilling Machine Operator)	
Number of sacks of bentonite used in well sealO sacks	Drilling Machine Operator's License No.	
Brand name of bentonite	Water Wall Contractor's Contractor	
Number of pounds of bentonite per 100 gallons	Water Well Contractor's Certification:	
of water lbs./100 gals.	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.	
Was a drive shoe used? Tyes I No Plugs Size: location ft.	1 1) to TO and I'm I also AN	
Did any strata contain unusable water? Yes No	(Person tirm or corporation) (Type or print)	
Type of water? depth of strata	Address 1972 BOV	HOHERNS
Method of sealing strata off	1 R Expalar	Inter De C
7/4	[Signed] (Water Well Contra	actor)
		Nove 25, 1972
Gravel placed from	Contractor's License No.	19. L. L. 19.