NOTICE TO WATER WELL CONTRACTOR The original and first copy
of this report are to be
filed with the

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

NC 8

WATER WELL REPORT
STATE OF OREGON
(Please type or print) NOV 19 1971

ate Well No. 5.1

(Do not write about this time ENGINEER Permit No.

(1) OWNER:	(10) LOCATION OF WELL:	No House-spin-
Name DESERT MAGIC, INC.	County Marrow Driller's well no	umber
Address P.O. BOX 216	SW 14 SW 14 Section 33 T. 5 NO.R. 26 E W.M.	
Boardman, Oregon	Bearing and distance from section or subdivision corner	
(2) TYPE OF WORK (check):	1320' North & 1320' East of SW Corner Sec 33	
New Well ♣ Deepening ☐ Reconditioning ☐ Abandon ☐	7	1 00#====
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed w	المر
(3) TYPE OF WELL: (4) PROPOSED USE (check):		
Potony 19 Driven I	Depth at which water was first found	51 ft.
Cable	Static level 51 ft. below land s	<del></del>
Dug Bored I Irrigation A Test Well Other	Artesian pressure lbs. per squar	e inch. Date
CASING INSTALLED: Threaded   Welded   16. "Diam. from   0.   ft. to   95.   ft. Gage   250.     250.     16.     16.   1	(12) WELL LOG: Diameter of well below casing Depth drilled 95 ft. Depth of completed well 95 ft. Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.	
Type of perforator used	MATERIAL	From To SWL
Size of perforations in. by in.		0 3
<u></u>	top soil	3 30 -
perforations from	coarse gray sand gravel sand & boulders	30 95
perforations fromft. toftft.	graver samu & bourders	
perforations from, it. to it.		
(7) SCREENS: Well screen installed? ★ Yes □ No		
Manufacturer's Name Johnson		
Type Model No	-	
Diam. 16 Slot size 50 Set from 80 ft. to 95 ft.		
Diam. Slot size Set from ft. to ft.		
(8) WELL TESTS: Drawdown is amount water level is lowered below static level		
Was a pump test made? ₩ Yes □ No If yes, by whom?Driller		
Yield: 1447 gal./min. with 29 ft. drawdown after 12 hrs.		
" " "		
" " "		
Bailer test gal./min. with ft. drawdown after hrs.		
Artesian flow g.p.m.		
Temperature of water Depth artesian flow encountered ft.	Work started 8-2 1971 Complete	
(9) CONSTRUCTION:	Date well drilling machine moved off of well	8-8 1971
Well seal—Material usedCement	Drilling Machine Operator's Certification:	
Well sealed from land surface to	This well was constructed under my	direct supervision.
Diameter of well bore to bottom of seal24in.	Materials used and information reported best knowledge and belief.	
Diameter of well bore below seal24 in.	[Signed] Steve moon	Date of 19 1971
Number of sacks of cement used in well seal90 sacks	(Drilling Machine Operator)	
Number of sacks of bentonite used in well seal sacks	Drilling Machine Operator's License No. 255	
Brand name of bentonite	Water Well Contractor's Certification:	
Number of pounds of bentonite per 100 gallons		
of water lbs./100 gals.	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.	
Was a drive shoe used? ☐ Yes X☐ No Plugs Size: location ft.		
Did any strata contain unusable water? Tyes X No	Name Desert Magic, Inc. (Person, firm or corporation) (Type or print)	
Type of water? depth of strata	AddressBox 216 Boardman, Oregon 97818	
Method of sealing strata off	[Signed] Howard Last therident	
Was well gravel packed? X Yes [ No Size of gravel: 1/8 to 3/8	[Signed] (Water Well Contr	actor)
Gravel placed from 51 ft. to 95 ft.	Contractor's License No Date Oct	