

ROTARY AIR DRILLED

TO WATER WELL CONTRACTOR
The original and first copy
of this report are to be
filed with the
ENGINEER, SALEM, OREGON 97310
within 30 days from the date
of well completion.

RECEIVED
STATE OF OREGON
STATE ENGINEER
SALEM OREGON
MORR 13

State Well No. 1/24-6
State Permit No.

1) OWNER:
Name MARION & Geneva Palmer
Address Fome, Oregon

(2) TYPE OF WORK (check):
New Well Deepening Reconditioning Abandon
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL: (4) PROPOSED USE (check):
Rotary Driven Domestic Industrial Municipal
Cable Jetted Irrigation Test Well Other
Dug Bored

CASING INSTALLED: Threaded Welded
10" Diam. from 0 ft. to 43 ft. Gage 1.250
" Diam. from ft. to ft. Gage
" Diam. from ft. to ft. Gage

PERFORATIONS: Perforated? Yes No.
Type of perforator used
Size of perforations in. by in.
perforations from ft. to ft.
perforations from ft. to ft.
perforations from ft. to ft.
perforations from ft. to ft.
perforations from ft. to ft.

(7) SCREENS: Well screen installed? Yes No
Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WATER LEVEL: Completed well.
Static level 5 ft. below land surface Date
Artesian pressure lbs. per square inch Date

(9) WELL TESTS: Drawdown is amount water level is lowered below static level
Was a pump test made? Yes No If yes, by whom?
Yield: gal./min. with ft. drawdown after hrs.
" " " " " "
" " " " " "
Bailer test gal./min. with ft. drawdown after hrs.
Artesian flow g.p.m. Date
Temperature of water Was a chemical analysis made? Yes No

(10) CONSTRUCTION:
Well seal—Material used Cement
Depth of seal 23 ft.
Diameter of well bore to bottom of seal 12 in.
Were any loose strata cemented off? Yes No Depth
Was a drive shoe used? Yes No
Did any strata contain unusable water? Yes No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? Yes No Size of gravel:
Gravel placed from ft. to ft.

(11) LOCATION OF WELL:
County MORROW Driller's well number 77
NE 1/4 SE 1/4 Section 6 T. 15 R. 24 W.M.
Bearing and distance from section or subdivision corner

(12) WELL LOG: Diameter of well below casing 10"
Depth drilled 133 ft. Depth of completed well 133 ft.
Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level as drilling proceeds. Note drilling rates.

MATERIAL	From	To	SWL
Top Soil SANDY	0'	8'	
GRAVEL & Boulders	8'	27'	
LAVA Rock BLACK	27'	36'	
Clay-yellow-SANDY	36'	43'	
Rock-grey	43'	75'	
Rock-BLACK	75'	79'	
Rock-LAVA-BROWN	79'	108'	
Rock-BLACK	108'	130'	
Rock-BLACK-BASALT	130'	133'	

Work started 9/10 1968 Completed 9/17 1968
Date well drilling machine moved off of well 9/17 1968

Drilling Machine Operator's Certification:
This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.
[Signed] Frank A. Curwe Date Jan 6, 1969
(Drilling Machine Operator)

Drilling Machine Operator's License No. 280

Water Well Contractor's Certification:
This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
NAME EDMOND BOEHR'S WELL DRILLING
(Person, firm or corporation) (Type or print)
Address BOX 414 OAKLAND ORE
[Signed] Edmond Boehrs
(Water Well Contractor)
Contractor's License No. 456 Date 1-9, 1969