NOTICE TO WATER WELL CONTRACTOR The original and first copy WATER WELL REPORT CE WELLATE OF OREGON State Well No 50/27E - 19ca of this report are to be filed with the STATE ENGINEER, SALEM, OREGON 97310 1 1977 (Please type or print) within 30 days from the date State Permit No. . WATER RESOURCES DEPT above this line) of well completion. SALFM. OREGON (10) LOCATION OF WELL: (1) OWNER County Morraul ITTI GOM Driller's well number NW 4 SUL 4 Section 19 T. SN R. 27 E Bearing and distance from section or subdivision corner (2) TYPE OF WORK (check): Block 40 New Well X Deepening [Reconditioning [Abandon [7] If abandonment, describe material and procedure in Item 12 (11) WATER LEVEL: Completed well. (3) TYPE OF WELL: (4) PROPOSED USE (check): Depth at which water was first found Rotary Driven [Domestic 🗌 Industrial 🗎 Municipal 😿 ft. below land surface. Date Irrigation | Test Well | Other Dug Bored Artesian pressure lbs. per square inch. Date CASING INSTALLED: Threaded [Diameter of well below casing . ft. to ft. Gage 4.4 " Diam, from ft. Depth of completed well Depth drilled 16 " Diam. from + 2.3 ft. to 5 6.5 ft. Gage + 250 Formation: Describe color, texture, grain size and structure of materials; ft. to .. and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata. PERFORATIONS: Perforated? | Yes | No. MATERIAL SWI. pe of perforator used Tennisharry Silty Sond Size of perforations ... perforations from . perforations from perforations from (7) SCREENS: Well screen installed? XYes | No Manufacturer's Name U.F. Jennsen Type Teles Stopped 129 Model No. 7
Diam 14/2 Slot size 125 Set from 56. — ft. to 66. — ft.
Diam Rise Stot Bize De Set Iron 1 Mars 4 10 453. — ft. 38,0 Drawdown is amount water level is lowered below static level (8) WELL TESTS: med, to course Was a pump test made? Yes Whom? Yield: 1400 gal./min. with [3] ft. drawdown after 24 hrs. Bailer test 100 4 gal./min. with 0 9ft. drawdown after 1/2 hrs. Artesian flow h/ONE g.p.m. emperature of water 54 Depth artesian flow encountered MONSE ft. Work started March 10 1977 Completed 703 Date well drilling machine moved off of well Well seal-Material used Cemant Grou Drilling Machine Operator's Certification: This well was constructed under my direct supervision. Materials used and information reported above are true to my Well sealed from land surface to 23.2 Diameter of well bore to bottom of seal 20 best knowledge and belief. Tohn L Esour Date April 23,19.7.7 Diameter of well bore below seal 17/2 in. 07 (Drilling Machine Operator) Number of sacks of cement used in well seal Drilling Machine Operator's License No. . Number of sacks of bentonite used in well seal Brand name of bentonite 1954 in a Mixe Number of points of pentonite per 100 cellons 05 C Water Well Contractor's Certification: This well was drilled under my jurisdiction and this report is 20 CAS Mawhile Ibs/100 gals true to the hest of my knowledge and belief. Was a drive shoe used? Yes ☐ No Plugs Size: location _____ ft. (Type or print) Did any strata contain unusable water?

Yes No Address ... Hermisten Ore. Type of water? depth of strata Method of sealing strata off Was well gravel packed? | Yes No Size of gravel:

ft. to

Gravel placed from

Contractor's License No. 5/6 Date AATI 23 1977