

NOTICE TO WATER WELL CONTRACTOR

MORR 1411

The original and first copy of this report are to be filed with the STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

REGISTERED WATER WELL REPORT

REGISTERED AUG 20 1968 STATE ENGINEER SALEM OREGON

MORR 1411

State Well No. 52/27-19

State Permit No. \_\_\_\_\_

(1) OWNER:

Name Fred Walker
Address Prineville, Oregon

(2) TYPE OF WORK (check):

New Well [x] Deepening [ ] Reconditioning [ ] Abandon [ ]

(3) TYPE OF WELL: (4) PROPOSED USE (check):

Rotary [x] Driven [ ] Domestic [ ] Industrial [ ] Municipal [ ]
Cable [ ] Jetted [ ] Irrigation [x] Test Well [ ] Other [ ]
Dug [ ] Bored [ ]

CASING INSTALLED:

8" Diam. from 0 ft. to 6.4 ft. Gage 250
" Diam. from ft. to ft. Gage
" Diam. from ft. to ft. Gage

PERFORATIONS:

Perforated? [ ] Yes [x] No
type of perforator used
Size of perforations in. by in.
perforations from ft. to ft.
perforations from ft. to ft.
perforations from ft. to ft.
perforations from ft. to ft.
perforations from ft. to ft.

(7) SCREENS:

Well screen installed? [ ] Yes [x] No
Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WATER LEVEL: Completed well.

Static level 39 ft. below land surface Date 8-17-68
Artesian pressure lbs. per square inch Date

(9) WELL TESTS:

Drawdown is amount water level is lowered below static level
Was a pump test made? [ ] Yes [ ] No If yes, by whom?
gal./min. with ft. drawdown after hrs.
Artesian flow g.p.m. Date
Temperature of water Was a chemical analysis made? [ ] Yes [ ] No

(10) CONSTRUCTION:

Well seal—Material used Buddled clay
Depth of seal 18 ft.
Diameter of well bore to bottom of seal 10 in.
Were any loose strata cemented off? [ ] Yes [x] No Depth
Was a drive shoe used? [x] Yes [ ] No
Did any strata contain unusable water? [ ] Yes [x] No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? [ ] Yes [x] No Size of gravel:
Gravel placed from ft. to ft.

(11) LOCATION OF WELL:

County Morrow Driller's well number
1/4 1/4 Section 19 T. 5 N R. 9 E. W.M.
Bearing and distance from section or subdivision corner
Borehole on South line of Sec 19 in City of Prineville, Oregon

(12) WELL LOG:

Diameter of well below casing 8"
Depth drilled 65 ft. Depth of completed well 65 ft.
Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level as drilling proceeds. Note drilling rates.

Table with columns: MATERIAL, From, To, SWL. Entries: Sand (0-5), Clay + small gravel (5-30), Gravel (30-63), Rock (63-65).

Work started 8-15 1968 Completed 8-17 1968
Date well drilling machine moved off of well 8-17 1968

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.

[Signed] Troy Huff Date 8-17, 1968
(Drilling Machine Operator)

Drilling Machine Operator's License No. 15

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

NAME TRAY SPIFFIN (Person, firm or corporation) (Type or print)

Address 925 HERNIMISTON AVE, HERNIMISTON OREG.

[Signed] Troy Huff (Water Well Contractor)

Contractor's License No. 65 Date 8-17, 1968