NOTICE TO WATER WELL CONTROL & C E V E

The original and first copy of this report are to be

AUG 15 1994 THE WELL REPORT

state engineer, salem, oregon 97370 ENC Triess type or print)
within 30 days from the date SALEM. OR (Do not write above this line) filed with the

State	Well No. 5N	127E-30
More State		
1458/		

	1958/		
(1) OWNER:	(10) LOCATION OF WELL:		
Name Wayne Schnell	County Morrew Driller's well nu	ımher	
Address Itagen, Orlhan		R. 27 E.	W.M.
	Bearing and distance from section or subdivision		W.MI.
(2) TYPE OF WORK (check):	Constant to m Section of Subdivision	m comer_	
New Well 🔂 Deepening 🗌 Reconditioning 🖺 Abandon 🗍			
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed w		
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 19	CII.	
Rotary Driven Domestic Mindustrial District Dist			7/- c /
Cable			1/28/72
	Artesian pressure lbs. per square		
(5) CASING INSTALLED: Threaded  Welded	(12) WELL LOG: Diameter of well b		155
8" Diam from ft. to 40 ft. Gage , 250	Depth drilled 300 ft. Depth of comple		
ft. to ft. Gage	Formation: Describe color, texture, grain size a		
	and show thickness and nature of each stratun	n and aquifer	penetrated.
PERFORATIONS: Perforated?	with at least one entry for each change of format position of Static Water Level and indicate princ	ion. Report eac ipal water-bea	h change in ring strata
Type of perforator used	MATERIAL		<del></del>
Size of perforations in. by in.	- TA4 . 1 ' Q	From To	SWL
perforations from ft. to ft.	1 ogsåte	0 1	
perforations from	Rock med gray	1 35° 35° 79	
perforations fromft. toft.	Prib Hack	79 113	_
	Rock med gray	1/3 /35	_
(7) SCREENS: Well screen installed? ☐ Yes ☑ No	Bassel	135 244	7
Manufacturer's Name	Basalk hard aran	244 256	;
Type Model No.	Rock black & aren Claraton	256 300	W.B.
Diam. Slot size Set from ft. to ft.			
Diam. Slot size Set from ft. to ft.			
(8) WELL TESTS: Drawdown is amount water level is			
iowered below static level			<del></del>
Was a pump test made?  Yes No If yes, by whom?		<del></del>	
Yield: gal./min. with ft. drawdown after hrs.			<del></del>
" " "		<del></del>	<del> </del>
an "			
Bailer test 6.5 gal./min. with 148 ft. drawdown after / hrs.			
Artesian flow g.p.m.			
nperature of water Depth artesian flow encountered ft.	Work started 7 - 20 19 72- Completed	7-28	1972
(9) CONSTRUCTION:	Date well drilling machine moved off of well	7-28	
	Duilling Wooking Organization Constitution Alexander		
Well seal-Material used Bentonte & Cenny	Drilling Machine Operator's Certification: This well was constructed under my	direct sune	rvicion
Well sealed from land surface toft.  Diameter of well bore to bottom of sealin.	Materials used and information reported a	bove are tru	ie to my
Diameter of well bore below seal	best knowledge and belief.	010	1 42
Number of sacks of cement used in well sealsacks	[Signed] (Drilling Machine Operator)	ateX././.5	4., 19./
Number of sacks of bentonite used in well seal / sacks	Drilling Machine Operator's License No	15	
Brand name of bentonite National			
Number of pounds of bentonite per 100 gallons	Water Well Contractor's Certification:		
of water lbs./100 gals.	This well was drilled under my jurisdic true to the best of my knowledge and belie	tion and this	report is
Was a drive shoe used? 🔀 Yes 🗆 No Plugs Size: location ft.			
Did any strata contain unusable water?   Yes  No	Name TROY GRIFFIN (Person, firm or corporation)	(Type or p	rint)
Type of water? depth of strata	Address 900 HERMISTON LVE, A	FEM 157	ON OPE
Method of sealing strata off	Tope Unil		*****
Was well gravel packed? [] Yes 💢 No Size of gravel:	[Signed] Troy Gruffi (Water Well Contract	tor)	••••••
Gravel placed from ft. to ft.	Contractor's License No. 65 Date		