NOTICE TO WATER WELL CONTRACTOR MORR 163 state Well No. 2/26-26cd The original and first copy WATER WELL REPORT OREG DE GE I VESTATE OF OREGON of this report are to be filed with the

Was well gravel packed?

Yes No

Gravel placed from

within 30 days from the date. AUG 17 1970 On not write about 1970 On	ove this line) 6 5 448
STATE ENGINEER (1) OWNER: SALEM ORGON	3
(1) OWNER: SALEM ORLUGAR	(10) LOCATION OF WELL:
Name Morrow County Fair Board	County Murow Driller's well number
Address Heppner, Olegan	1.E 1/4 5.W 1/4 Section 26 T. 2 S. R. 26 E. W.M.
	Bearing and distance from section or subdivision corner
(2) TYPE OF WORK (check):	
New Well Deepening Reconditioning Abandon	
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 26 ft.
Rotary Driven Domestic Maindustrial Municipal D	Static level 40 ft. below land surface. Date \$16170
Cable	
Dug ☐ Bored ☐ ☐ Irrigation 🔀 Test Well ☐ Other ☐	Artesian pressure hs. per square inch. Date
CASING INSTALLED: Threaded Welded	(12) WELL LOG: Diameter of well below casing
8 " Diam from 0 ft. to 3 4 ft. Gage 258	
"Diam. from	
"Diam, from ft. to ft. Gage	Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated,
	with at least one entry for each change of formation. Report each change in
PERFORATIONS: Perforated? Yes No.	position of Static Water Level and indicate principal water-bearing strata.
Type of perforator used	MATERIAL From To SWL
Size of perforations in. by in.	Topsoil 0 3
perforations fromft. toft.	Claristone yellow 3 25
perforations from ft. to ft.	Rrck, Alcel 25 34
perforations from ft. to ft.	Basall 34 60
POLICE PO	Basalt, grey hard 60 118
(7) SCREENS: Well screen installed? Yes Y No	Basaly 1 118 140
Manufacturer's Name	Basalt gun 140 165
Type Model No.	Basals Charge broken 165 168
Diam. Slot size Set from ft. to ft.	(water bearing)
Diam. Slot size Set from ft. to ft.	Basalr 168 170
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	
lowered below static level	
Was a pump test made?	
Yield: gal./min. with ft. drawdown after hrs.	- Part Control of the Part
н н	W 1 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2
" " "	
Batter test 300 gal./min. with 20 ft. drawdown after / hrs.	A CAMP CAMP CAMP
Artesian flow g.p.m.	Work started 7-21 1970 Completed 8-7 1970
Temperature of water Depth artesian flow encounteredft.	TOTAL BOOK OF THE PARTY OF THE
CONSTRUCTION:	Date well drilling machine moved off of well 3-7 19 70
Carra and V	Drilling Machine Operator's Certification:
2.//	This well was constructed under my direct supervision.
Well sealed from land surface toft. Diameter of well bore to bottom of sealfn.	Materials used and information reported above are true to my best knowledge and belief.
Diameter of well bore to bottom of seal in. Diameter of well bore below seal in.	1 and U-11- G-771
	(Drilling Machine Operator)
Number of sacks of cement used in well sealsacks Number of sacks of bentonite used in well sealsacks	Drilling Machine Operator's License No. 15
\$ -	
Brand name of bentonite Number of pounds of bentonite per 100 gallons	Water Well Contractor's Certification:
Y- 400 I-	This well was drilled under my jurisdiction and this report is
of water	true to the best of my knowledge and belief.
Did any strata contain unusable water? Yes No	Name TROY GRIFFIN (Person, firm or corporation) (Type or print)
	Address 925 HERMISTON AVE, HERMISTON ORE
Type of water? depth of strata	61 11-11-
Method of sealing strata off	[Signed] (Water Well Contractor)
Was well gravel marked? Was Was Circ of gravel.	- (i i i i i i i i i i i i i i i i i i

Contractor's License No. .

Size of gravel:

19.7.0