NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report are to be filled with the STATE ENGINEER, SALEM, OREGON 97310 Within 30 days from the date of well completion. STATE ENGINEER, SALEM, OREGON 97310 MAR 9 19 (Ruless type or print) The print No. (Do not write above this link) TE ENGINEER SALEM, OREGON STATE ENGINEER SALEM, OREGON STATE ENGINEER SALEM, OREGON

SALEM OR GON

(1) OWNER:	(11) LOCATION OF WELL:			
Name Porter-Peringer, Inc.	County Morrow Driller's well number			
Address E 1727 20th., Spokane, Washington	14 14 Section 8 T. 2	N R.	27E	W.M.
	Bearing and distance from section or subdivision corner			
(2) TYPE OF WORK (check):	2,888' S & 1,238' W. of N. E. Corner			
New Well (Deepening □ Reconditioning □ Abandon □	of Section 8			
If abandonment, describe material and procedure in Item 12.				
(3) TYPE OF WELL: (4) PROPOSED USE (check):	(12) WELL LOG: Diameter of well		. 1	2½
Rotary Driven Domestic Industrial Municipal Domestic	900			
Dug Bored I Irrigation Test Well Other	Economica It. Depth of comp			ft.
CASING INSTALLED: Threaded Welded December 10 min from 170 ft. to 170 ft. Gage 250	Formation: Describe color, texture, grain size and show thickness and nature of each strat with at least one entry for each change of form in position of Static Water Level as drilling position.	um and a mation. R	aquifer pe leport eac	netrated, h change
14 "Diam. from 165 ft. to 370 ft. Gage • 250	MATERIAL		1	<u> </u>
		From	То	SWL
	Overburden, White Cement	1	-	
PERFORATIONS: Perforated? Yes No.	Grave1	0	30	
pe of perforator used	Gray Clay	30	50	
Size of perforations in. by in.	River Gravel & Sand Red Clay	50	80	
perforations from ft. to ft.	Black Gravel & Sand	80	120	
perforations from ft. to ft.		120	150	
perforations from ft. to ft.	Gray Basalt Rock Black Gravel	150	260	
perforations from ft. to ft.	Broken Gray Basalt	260	280	
perforations from ft. to ft.	Black Gravel	280	300	
(7) CODEENC.	Broken Black Basalt	300	320	
(7) SCREENS: Well screen installed? ☐ Yes ☐ No	Solid Black & Gray Basalt	370		
Manufacturer's Name Model No.	Green Clay	500	500 520	
	Hard Basalt	520	630	
Diam. Slot size Set from ft. to ft.	Porous Basalt	630	650	370
Diam. Slot size Set from ft. to ft.	Hard Basalt	650	735	
(8) WATER LEVEL: Completed well.	Porous Basalt	735	745	
Static level 370 ft. below land surface Date 10-28-6		745	800	370
sian pressure lbs. per square inch Date				
(9) WELL TESTS: Drawdown is amount water level is lowered below static level				
Was a pump test made? 🗌 Yes 🧸 No If yes, by whom?				
Yield: gal./min. with ft. drawdown after hrs.	Work started 9-4 19 69 Comple	ted	1-9	1970
" "	Date well drilling machine moved off of well	1	1-14	1969
<u>"</u> " "	Drilling Machine Operator's Certification:			
Bailer test 0 gal./min. with ft. drawdown after hrs.	This well was constructed under my d	lirect sur	ervision.	Mate-
Artesian flow g.p.m. Date	rials used and information reported abo	ve are t	rue to r	ny best
Temperature of water Was a chemical analysis made? Yes No	[Signed] (Srilling Machine Overstor)	Date	11-20	, 19. ⁶⁹
(10) CONSTRUCTION:	Drilling Machine Operator's License No.	52	8	
Well seal—Material used Cement Depth of seal 0 to 170				
- L	Water Well Contractor's Certification:			
Diameter of well bore to bottom of sealin.	This well was drilled under my jurisd true to the best of my knowledge and beli	liction ar ief.	nd this r	eport is
Were any loose strata cemented off? Wes I No Depth 375-430	NAME Morrison-Knudsen Company, Inc.			
Was a drive shoe used? □ Yes ਨੂੰ No Did any strata contain unusable water? □ Yes ਨੂੰ No	(Person, firm or corporation)	(Typ	e or print)	(MACHEN /
	Address 212 S. E. First, Pendl	eton,	Oregon	97801
Type of water? depth of strata	- 1 11	F#46616747177773	ACCREMINATION AND ADDRESS OF THE PERSON ADDRESS OF THE PERSON AND ADDRESS OF THE PERSON ADDR	~~~~/
Method of sealing strata off	[Signed] Signed	غرب		<u></u>
Was well gravel packed? ☐ Yes 🛣 No Size of gravel:	(Water Well Contra			
Gravel placed fromft. toft.	Contractor's License No Date		3-1	19.70